

Product Guide**A 4486** 1 Zone Line Level Paging Microphone

A 4486 1 Zone Line Level Paging Microphone



Overview

An elegant desk top single zone paging microphone with pre-announcement chime, balanced line level output and 3.5mm BGM input. The base is a robust heavy duty design coupled with a dynamic cardioid gooseneck microphone. Connection to the microphone is via economical industry standard Cat 5 (or similar) cable. Connections for remote power (24V DC) and the balanced audio output are via an 8 pin RJ45 socket. Output volume is adjustable and the unit is supplied with an inbuilt pre-announcement chime (selectable internally). The high level balanced output allows transmission over 300m without interference. Requires A 4487 interface box & M 9391A 24V DC plugpack to operate.

Key Features

- ✓ **Australian made**
- ✓ **10 year manufacturer warranty with local product support**
- ✓ Heavy duty metal desktop case
- ✓ Easy installation using standard Cat5e UTP cable.
- ✓ Power via standard 24V DC.
- ✓ Pre-announcement chime.
- ✓ Can be installed up to 300m from amplifier.
- ✓ Includes 3.5mm input for BGM program source from your phone.

Specifications

Electrical

Mic frequency response:	100Hz - 10kHz
Mic polar pattern:	Cardioid (unidirectional)
Power supply:	24V DC

Mechanical

Mic gooseneck:	≈325mm
Base unit (mm):	137L x 113W x 59H

Accessories (sold separately)

A 4487 Interface box
M 9391A 24V DC power supply

About Redback® Public Address Products

Redback® products are proudly designed, engineered and manufactured in Australia.

Each unit is covered by a comprehensive 10 year parts and labour warranty. Redback® offers rock solid reliability from over 30 years experience in the commercial sound industry. Redback® offer locally available servicing and parts, plus the ability to offer feedback direct to the manufacturer.