

ZAPGUARD® PRO SURGE FILTERS



Designed to provide a high degree of secondary protection to critical circuits in harsh environments, the **PowerShield ZapGuard Pro Range** of surge filters is available for pluggable as well as hard wired installations. These devices are particularly suitable for use with UPS systems, servers and specialised industrial sites.

PORTABLE SERIES 10A | 16A

The ZapGuard series of portable filters are designed to provide secondary protection and are particularly suitable for use with plug in UPS systems, servers, instrumentation, POS systems, specialised industrial and commercial portable equipment where a high degree of protection is required.



- IEC input and output
- 2 part display
- 3 stage, 3 mode protection
- LC filter network
- Rugged IP24 enclosure
- 10A and 16A versions
- Surge protection and EMI / RFI filter
- 40kA I_{max} L-N. 60kA all modes

PANEL MOUNT SERIES SINGLE PHASE 40A | 63A

The 40A and 60A panel mount models are particularly suitable for use in single phase circuits with critical equipment such as UPS, control systems, IT devices etc. Status of the unit is indicated by LED indicators on the top face.

- Panel mounted surge protection & filter
- Hardwired input/output terminals
- 2 part display
- Remote alarm contacts
- 3 stage, 3 mode protection
- Metal terminal Cover (PSZTC) optional



WALL MOUNT FILTERS, THREE PHASE 63A TO 800A

Wall Mount Surge Filters are configured in a 3 stage, 7 protection mode topology. These models are designed to provide primary AND secondary protection to key circuits with multiple loads. They provide a high degree of protection to dedicated single load devices such as UPS, servers etc which are directly connected to the filter.

- Panel mounted surge protection & filter
- Surge counter
- Rugged IP20 enclosure
- 3 phase, 3 stage, 7 mode protection
- 63A to 800A current rated
- 4 part led display
- Remote alarm contacts



AUSTRALIAN DESIGNED
POWER PROTECTION
SOLUTIONS



ZAPGUARD PRO PSZ PORTABLE AND PANEL MOUNTED SERIES

SERVICE RATING	10A & 16A	40A	63A	63A THREE PHASE	125A THREE PHASE	200-800A THREE PHASE
Model Number	PSZ10APF & PSZ16APF	PSZ40APF	PSZ63APF	PSZ363APF	PSZ3125APF	PSZ3200APF, PSZ400APF, PSZ800APF
Nominal voltage Un	200-250VAC, Single phase, 48-62Hz			200-250VAC, Three phase, 48-62Hz, TT, TN systems		380-440VAC, Three phase, 4 wire + E, 47-60Hz
Ports	2 port					
MCOV Uc	320Vac L-N, 255VAC N-E				350Vac L-N, 255VAC N-E	320Vac L-N
TOV	350Vac L-N			446Vac L-E each phase	440Vac/120min	446VAC
Protection modes	L-N, N-PE, L-PE			L1, L2, L3-E, N-E primary; L1, L2, L3-N secondary		
I _{max} 8/20us	40kA L-N, 10kA L-E, 10kA N-E	50kA L-N, 10kA L-PE, 10kA N-E		Primary 100kA L1,L2,L3-E Common 50kA N-E Secondary 60kA L1,L2,L3-N	150kA each mode primary 50kA each mode secondary	120kA each mode primary 50kA each mode secondary
I _{nom} 8/20us	20kA L-N, 5kA, L-E, N-E	50kA L-N, 10kA L-PE, 10kA N-E		50kA each mode primary 30kA each mode secondary	50kA each mode primary 25kA each mode secondary	50kA each mode primary 20kA each mode secondary
SCW (1 sec)	—			29kA		
Response time	<25ns			—		
Service type	1 Phase, Line/Neutral/Earth 10A or 15A IEC to IEC	1 Phase, Line/Neutral/Earth 40A CB or 63A CB		3 Phase. TT, TN systems		
Topology	Stage 1. L1, L2, L3-N MOV, N-E GA Stage 2. Low pass LC network Stage 3. L-N MOV.			Stage 1. L1, L2, L3-E MOV, N-E GA Stage 2. Low pass LC network Stage 3. L-N MOV.	Stage 1. L1, L2, L3-N MOV, N-E GDT Stage 2. Low pass LC network Stage 3. L-N MOV/GDT	Stage 1. L1, L2, L3-N MOV,s N-E Spark Gap Stage 2. Low pass LC network Stage 3. L1, L2, L3-N MOV,s
Location category	Indoor					
Degree of protection	IP24	IP20		IP20	IP20	IP50
Thermal dissipation	—			120W each phase @ full load, 3 phase, 63A	750W @ full load, 3 phase, 125A	120W @ full load, 3 phase, 400A
Termination size	—	Single-strand 35mm ² ; multi-strand 25mm ²				Bolt on M10 lugs 400A and 800A
Mounting	Portable	Wall mounting				
Operating temp	−10°C to +50°C	−10 to 60°C, 0 to 90%RH (non-condensing)				−10 to 70°C, 5 to 95%RH (non-condensing)
Dimensions D x W x H (mm)	152 x 133 x 55	220 x 143 x 48		510 x 370 x 140	520 x 520 x 170	900 x 760 x 245
Weight (kg)	0.8	2		18	34	80
Indicators	2 x LEDs. Blue OK. Red Failure			4 part display. Blue OK	4 part display. On OK. Off fault	7 part status display showing primary and secondary protection status
Alarms	—	Dry contact relay. NC/Com/NO. 250Vac/32Vdc, 5A				

Specifications are subject to change without prior notice.