

Data Sheet

C 1061 High Power IP56 100V PA Speaker - White
C 1062 High Power IP56 100V PA Speaker - Black



Includes sealed connection panel with PG11 cable gland. Plus second PG11 cable gland and knockout for use with loop in, loop out wiring.

Description

This all weather long throw PA speaker features a two-way driver, including 5.25-inch woofer and 1-inch tweeter for PA sound projection. It offers the flexibility of 8 ohm or 100V line settings with a total power handling up to 240W and max 100V power tap of 60W. This makes it ideal for dispersing sound across large open areas like parks, stadium concourses and public open spaces. The connection panel on the rear offers rotary power tap selection and loop in, loop out terminals for simply termination in the speaker chain (extra cable gland and knock out on rear panel provided). All connections are covered by a sealed screw in panel preventing moisture and dust ingress.

Specifications

Power Tapping:	7.5W, 15W, 30W and 60W
Max Handling Power:	100W
Speaker:	135mm (5.25") woofer + 25mm (1") tweeter
Input Voltage:	100V Line
Sensitivity:	88dB (1w/m)
Max SPL:	106dB
Frequency Response:	70-18KHz
Dispersion (1KHz):	Horizontal 105°, Vertical 85°
Connection Method:	Screw terminal
Connection Panel:	PG11 gland fitted to plate with knockout for second PG11 gland (included)
Mounting Method:	Wall mounting bracket (powdercoated steel)
IP Rating:	IP56
Colour:	White / Black
Dimensions:	180W x 175D x 325Hmm (exc. bracket)
Weight:	5.2kg
Mounting Requirements:	5mm hex