Data Sheet

C 2260 100mm (4") 100V 5W Alum. Grille Ceiling Speaker White AS ISO7240.24 **C 2261** 100mm (4") 100V 5W Alum. Grille Ceiling Speaker Black AS ISO7240.24



Description

C 2260 & C 2261 are ceiling mount speakers certified to the AS ISO7240.24 standard for fire & evacuation announcements in buildings. Each speaker is fitted with a fire retardant speaker/transformer dome and is fitted with oversized cable glands and terminal blocks for easy on site termination. The speaker utilises the One-Shot 'snap fit' mounting system.

Specifications

Rated Noise Power	5 Watts (100V line)
Power Taps & Impedance (100V line)	0.33W (30kΩ), 0.66W (15kΩ), 1.25W (8kΩ), 2.5W (4kΩ), 5W (2kΩ)
Sensitivity	89dB (1W @ 1m), 77dB (1W @ 4m)
Maximum Sound Pressure Level	96dB (5W @ 1m), 84dB (5W @ 4m)
Frequency Response	100Hz - 15kHz
Coverage Angle (-6dB)	500Hz: >180°, 1000Hz: 180°, 2000Hz: 160°, 4000Hz 75°
Environmental Type	A (for indoor applications as per standard)
Speaker Component	100mm (4") paper cone speaker
Mounting Hole	140mmØ
Mounting Method	3 x plastic spring loaded clip
Line Monitoring	Yes, 22µF bipolar capacitor
Applicable Cable	2.5mm² (14AWG) max conductor area
Connection	4 way screw terminal
Finish	White (C 2260) or black (C 2261) flame retardant ABS grille (ABS AF312C) Clear Flame retardant ABS spring clips (Makrolon 6557) Red flame retardant ABS transformer dome cover (Starex VH-0800) Powdercoated aluminium grille insert (RAL9003 white, RAL9004 black)
Dimensions	159Ø x 65Dmm
Weight	710g
Quantities	24 per carton, 720 per pallet.

Test Method

This specification data was measured in an anechoic chamber, according to the AS ISO7240.24.

Reference axis: Axis is on the centre of the grille surface and perpendicular to the grille surface.

Reference plane: Plane is on the grille surface and perpendicular to the reference axis.

Horizontal plane: Plane is containing the reference axis and perpendicular to the reference plane.

Dimensions (mm)





