

CSIRO Verification Services Clayton, Victoria, Australia +61 13 0036 3400 https://activfire.csiro.au

## **Certificate of Conformity**

Certificate num.	Registration date	Version Va		Valid until	
afn - 2685	22.4 2222	Number	Issue date	22.4	Page <b>1</b> of <b>3</b>
atp - 3685	29-Apr-2022	2	22-Mar-2022	30-Apr-2024	_

### **Product designation**

Redback, Model CF2238/CF2239, type A, indoor, flush mount, emergency sound-system loudspeaker

(Refer to the Schedule/enclosures for further specified details)

### Agent/distributor

Altronic Distributors Pty Ltd 174 Roe Street, PERTH, WA, AUSTRALIA, 6000

### Registrant

Altronic Distributors Pty Ltd 174 Roe Street, PERTH, WA, AUSTRALIA, 6000

#### Producer

Altronic Distributors Pty Ltd 174 Roe Street, PERTH, WA, AUSTRALIA, 6000

### **Conformance criteria and evaluation**

The Redback, Model CF2238/CF2239, type A, indoor, flush mount, emergency sound-system loudspeaker has been evaluated and verified as conforming with the relevant requirements of the following criteria.

1. Australian Standard AS ISO 7240.24:2018, 'Fire detection and alarm systems - Part 24: Fire alarm loudspeakers'.

### Limitations/conditions of conformance

Limitations/conditions of conformance, where identified on this certificate, are derived from qualifications from evaluation(s) for conformity and/or other related technical documentation. All details with respect to design, assembly and installation instructions and restrictions should be checked against the producer's current technical manual/data sheets and the requirements of the Authority having Jurisdiction.

This certification is issued within the scope of CSIRO Verification Services – Rules governing ActivFire Scheme and is valid only for the product(s) as submitted for evaluation and verification of conformity, subject to the following conditions.

- Reference to details, limitations and requirements, where documented as a schedule/enclosure with this certificate.
- The Registrant is responsible for their attestation of conformity and ensuring that on-going production complies with the conformance criteria defined in this certificate.
- This certificate will not be valid if any changes or modifications are made to the product which have not been notified and validated by CSIRO Verification Services.
- This certificate is subject to periodical re-validation upon verification that all requirements, as determined by the conformity assessment body, continue to be satisfactorily met by the Registrant.
- This certificate may only be reproduced in its published form, without modification and inclusive of all schedules/enclosures.
- Any changes, errors or omissions, must be submitted in writing and if necessary or requested, substantiated with relevant evidence.
- Any representations, such as advertising or other marketing related activities or articles shall reflect the correct contents of this certificate and conform with all relevant trade practices .and consumer protection legislation and regulations.
- Any terms or conditions of use as applicable to content and documentation as published or accessed through web sites administered by the CSIRO Verification Services.

Issued by

Kai Loh

Executive Officer - ActivFire Scheme





### Schedule to

# **Certificate of Conformity**

Certificate num. Registration date		V	ersion	Valid until	
afp - 3685	29-Apr-2022	Number 2	Issue date 22-Mar-2023	30-Apr-2024	Page <b>2</b> of <b>3</b>

### **Producer's description**

The Redback, Model CF2238/CF2239, type A, indoor, flush mount, emergency sound-system loudspeaker is designed to be fitted into a suspended ceiling to provide emergency warning audible broadcasts.

This equipment is fitted with a 200 mm diameter paper cone speaker driver and a co-axial tweeter, and is rated for a maximum power output of 15 W when provided with an input signal of 100 Vac. Five taps are provided on the included transformer for operating at a range of output levels.

The Redback, Model CF2238/CF2239, type A, indoor, flush mount, emergency sound-system loudspeaker has a perforated aluminium circular front grill, approximately 265 mm in diameter, with a concentric pattern of holes, plus a clip-on rear cover which is fitted with two lock-nut cable glands for connection to an emergency sound system. It is fitted with six retaining clips.

The Redback, Model CF2238/CF2239, type A, indoor, flush mount, emergency sound-system loudspeaker is intended for indoor applications.

### **Technical specification**

The following details are a representative extract of the technical specification for the Redback, Model CF2238/CF2239, type A, indoor, flush mount, emergency sound-system loudspeaker and may be subject to change. Complete and current details should be determined from the designated producer's technical manual/data sheets.

#### Schedule of variant designations

The following is a schedule of validated variant designations of the certified/listed equipment.

Variant			
Туре	Ident.	Description	Colour
Nandal	CF2238	Turne A landerer fluide recount arrespondence and existence landerer land	White housing and grill
Model	CF2239	Type A, indoor, flush-mount, emergency sound-system loudspeaker	Black housing and grill

### Schedule of properties/characteristics

The following schedule is an extract of physical and operational properties/characteristics of the certified/listed equipment.

Rated noise power	15 Watts (100V line)
Power taps & impedance (100V line)	1.25W (8kΩ), 2.5W (4kΩ), 5W (2kΩ), 10W (1kΩ), 15W (668Ω)
Sensitivity	90dB (1W @ 1m), 78dB (1W @ 4m)
Maximum sound pressure level	101dB (15W @ 1m), 89dB (15W @ 4m)
Frequency response	100Hz - 20kHz; 100Hz-16kHz: 0±8dB
Coverage angle (-6dB)	500Hz: > 180°, 1000Hz: 160°, 2000Hz: 80°, 4000Hz: 70°
Environmental	Type A (for indoor applications as per standard)
Speaker component	200mm (8") paper cone speaker + coaxial tweeter
Mounting hole	246mmØ
Mounting method	6 x plastic spring loaded clip
Line monitoring	Yes, 22µF bipolar capacitor
Applicable cable	2.5mm² (14AWG) max conductor area
Connection	4 way screw terminal
Finish	White (CF2238) or black (CF2239) flame retardant ABS grille (ABS AF312C) Clear Flame retardant ABS spring clips (Makrolon 6557) Red flame retardant ABS transformer dome cover (Starex VH-0800)
	Powdercoated aluminium grille insert (RAL9003 white, RAL9004 black)
Dimensions	266Ø x 127 mm D
IP rating	IP 21C
Weight	1.95 kg

# Schedule to Certificate of Conformity

Certificate num.	num. Registration date		ersion	Valid until	
afp - 3685	29-Apr-2022	Number <b>2</b>	Issue date 22-Mar-2023	30-Apr-2024	Page <b>3</b> of <b>3</b>

### **Supplementary information**

### **Schedule of relevant articles**

The following schedule is an extract of articles significant and/or related as evidence of conformity.

Reference			Date issued		
Ident. type	Ident.	Title / description	(or date validated)	Source	
Report	XF3385/R5	Evaluation for Conformity of the Redback, Model CF2238/9, 15 W, Type A, indoor, flush mount, emergency sound-system loudspeaker to the requirements of AS ISO 7240.24:2018	13-Jan-2022	CSIRO, Fire Systems Laboratory, AU	
Data Sheet	CF2238 CF2239	Redback Data Sheet CF2238 200mm (8") 100V 15W Coaxial Ceiling Speaker White AS ISO7240.24 CF2239 200mm (8") 100V 15W Coaxial Ceiling Speaker Black AS ISO7240.24 (CF2238 Datasheet.pdf)	18-Nov-2021	Altronic Distributors Pty Ltd, WA, AU	