

# Sealed Lead Acid (SLA) Batteries

## 12V 9AH - 6.3mm/F2 Terminal

### Model: S 4543



This 12V 9Ah sealed lead acid (SLA) battery is a compact battery for powering 12V equipment. It is commonly used in battery back up systems, alarm and communications systems and UPS units. Fitted with 6.3mm/F2 tab terminals, these batteries are easily user replaced in most equipment they are used in. Cells are fully sealed to prevent any leakage of electrolyte.


Our range of Powerhouse SLA batteries are from a quality supplier and are graded for use in UPS systems. We have found the quality of SLA batteries varies considerably between suppliers and often cheaper units have a shorter life span.

**ActivFire Listed (afp3824). Conforms to IEC 60896-21:2004 and IEC 60896-22:2004.**


Cell per unit	6	Ambient temperature	
Nominal Voltage (V)	12	Charge	0°C (32°F) to 40°C (104°F)
Nominal Capacity (Ah)	9Ah @ 20 hours rate F.V(1.75/cell)	Discharge	-15°C (5°F) to 50°C (122°F)
Weight	Approx 2.65 kg (5.84Lbs.)	Storage	-15°C (5°F) to 40°C (104°F)
Internal Resistance (1KHz)	18mΩ	Max charge Current	
Max Discharge Current (5s)	135A (5s)	Cycle use :	Max charge current : 2.52A
Battery Life :	Stand by : 3~5 years		Charge voltage: 14.4V to 15.0V
Terminal Type	F2	Stand by :	Charge voltage: 13.5V to 13.8V
Container Material	ABS(Option : 94-HB & 94V-0 flame retardant case)		



DIMENSIONS	Length	Width	Height	Total Height
Unit: mm	151±1	65±1	94±1	100±1
Unit: inch	5.94±0.04	2.56±0.04	3.70±0.04	3.94±0.04



mm(inch)



F2

Constant current discharge characteristics Unit:A(25°C 77°F)										
F.V/Time	5MIN	10MIN	15MIN	30MIN	60MIN	2HR	3HR	5HR	10HR	20HR
1.60V	37.00	25.00	17.00	9.98	5.21	3.12	2.40	1.52	0.85	0.46
1.67V	36.00	24.10	16.20	9.16	5.18	3.00	2.34	1.50	0.76	0.45
1.70V	34.00	23.30	15.50	8.75	5.14	2.97	2.25	1.48	0.76	0.44
1.75V	32.00	22.10	14.60	8.28	5.06	2.90	2.20	1.45	0.76	0.42
1.80V	30.00	20.20	14.00	7.92	4.99	2.82	2.15	1.40	0.75	0.40

Constant power discharge characteristics Unit:W(25°C 77°F)										
F.V/Time	5MIN	10MIN	15MIN	30MIN	60MIN	2HR	3HR	5HR	10HR	20HR
1.60V	432.0	261.6	208.8	120.0	71.5	37.3	25.9	19.3	9.76	5.20
1.67V	417.4	255.6	204.7	119.0	70.5	37.2	25.5	19.2	9.70	5.20
1.70V	400.1	250.8	200.1	118.0	70.3	37.0	25.4	19.0	9.58	5.10
1.75V	376.6	240.2	194.1	116.0	69.5	36.4	25.1	18.8	9.52	5.00
1.80V	325.4	230.4	185.6	113.0	68.8	36.0	25.1	18.6	9.30	5.00


# Sealed Lead Acid (SLA) Batteries

## 12V 9AH - 6.3mm/F2 Terminal


### Model: S 4543




#### Battery Discharge Characteristics (25°C/77°F)




#### Battery Charge Characteristic for standby use




#### Temperature Effects in Relation to Battery Capacity




#### Temperature Effects on Long Term Float Life



#### Cycle Service Life



#### Self Discharge Characteristics



#### Charging Procedures

Application	Charge Voltage(V/cell)			Max. Charge Current
	Temperature	Set Point	Allowable Range	
Cycle Use	25°C(77°F)	2.45	2.40-2.50	0.25C
Standby	25°C(77°F)	2.275	2.25-2.30	

#### Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/cell	1.75	1.70	1.65	1.60
Discharge Current (A)	0.2C > (A)	0.2C < (A)	0.5C < (A)	(A) > 1.0C