

▼ Subwoofers

Ceiling Mount 240W Subwoofer 4 Ohm/100V



Note: Due to the weight of the speaker, we recommend the unit be tethered to the ceiling with H 3900 safety chain.

High power commercial grade 10" subwoofer for providing additional low end response to foreground music and hi-fi applications. Built in 100V line transformer makes it suitable for integration with commercial systems in fashion boutiques, shopping centres, gymnasiums etc. Enclosed metal dome offers physical protection and extends bass response. Requires 330mmØ ceiling cutout. If mounting into a tiled ceiling, the C 1066 tile bridge should be utilised for a secure installation. Ideally paired with A 4861 subwoofer amp - see page 55.

Rated power: 240W @ 4Ω
 Power taps: 60, 120, 240W
 Max SPL: 112dB
 Frequency response: 30Hz - 15KHz
 Weight: 7.5kg
 Dimensions (mm): 360 x 330Dmm

Price Each	RRP	2+	4+
C 1065	669.00	599.00	549.00
C 1066 Ceiling tile bridge to suit	28.75	25.50	23.25

Low Profile Ceiling/Floor/Wall Mount Subwoofers



Can be ceiling suspended using H3319 eye bolts.

These ultra compact passive subwoofers feature 4 x 4" long throw drivers in a tuned enclosure designed for installation in domestic and commercial sound systems. Its versatile design allows it to be freestanding, attached to the wall behind a couch, or mounted to the ceiling using suitable hardware. 4 x M6 holes are provided for attachment to a wall bracket or suspended on a commercial ceiling cable tray (as is common in open ceiling venues). It is ideal for use in cafes, restaurants, small bars etc and is also well suited to any domestic entertaining area. Ideally paired with a dedicated subwoofer amplifier, such as the Redback A 4861 - see page 55.

Rated power: 200W @ 8 Ohm
 Max SPL: 112dB
 Frequency response: 45Hz - 150Hz
 Connection: Spring terminal
 Weight: 7.8kg
 Dimensions (mm): 375W x 375D x 116H

Price Each	RRP	2+	4+
C 5215 White	499.00	459.00	419.00
C 5216 Black	499.00	459.00	419.00
H 3319 M6 eye bolts for ceiling rigging	5.95		
P 8099 Wall bracket	25.00		

10" Outdoor 150W Subwoofer Speaker



Fitted with downward firing 10" sealed subwoofer driver.

This outdoor 150W passive subwoofer speaker is designed to be placed virtually anywhere outdoors for added low end bass response for commercial and domestic music systems. Its unique ABS enclosure can be placed on the floor and secured using the included eye bolt. It is ideal for use in cafes, restaurants, small bars etc and is also well suited to any domestic entertaining area. Ideally paired with a dedicated subwoofer amplifier, such as the Redback A 4861 - see page 55.

Rated power: 150W @ 4Ω
 SPL 1W @ 1m: 86dB
 Max SPL: 108dB
 Frequency response: 50Hz - 300Hz
 Weight: 12kg
 Dimensions (mm): 310H x 420Ømm

Price Each	RRP	2+	4+
C 5220	395.00	355.00	315.00

180W Active Sub-Woofers Amplifier Module



This completely self-contained amplifier module simply fits into the back of a subwoofer cabinet. Automatically springs into life from the standby mode once a signal is received. The volume and crossover frequency controls together with the phase correction switch enables desired low frequency system reproduction. Installation can be completed in just minutes, simply make a 235mmH x 175mmW cutout into the back of the enclosure and slip in the module. The unit is supplied with a foam seal surround so just screw it straight on, it's that easy! Overall depth is 110mm.

Features - Auto power on/off with signal presence - High & low level inputs & outputs
 - High level outputs - Volume control - Short circuit output protection - Active crossover variable from 20Hz - 200Hz - Phase reversal switch

Power: 180W Max @ 4Ω (0.5% THD)
 Frequency response (variable): 20Hz - 200Hz
 Roll off rate: 6dB/octave
 S/N ratio: >64dB
 Auto turn on sensitivity: 21mV
 Auto power off time: 15-20 minutes
 Input: (Line) 47kΩ, (speaker) 200Ω

Price Each	RRP	2+	4+
A 2451	249.00	225.00	199.00
C 3088 Optional 8" Woofers	59.00		