



15V - 30V Multi-Tapped 1A Max





Primary voltage: 240V AC
 Total VA rating: 30VA
 Insulation: Class E (120 °C)
 Magnetising current: <80mA
 Temperature rise: <65 °C
 Regulation: ≈8%
 External AC fuse (required): 500mA
 Thermal fuse: 125 °C
 Weight: ≈1kg
 Primary connection: 200mm fly leads
 Secondary connection: Solder tags

Must be used with a standard 500mA external AC fuse.

Price Each	RRP	4+	10+
M 6672L	22.50	20.25	18.00

6V - 15V Multi-Tapped 2A Max





Primary voltage: 240V AC
 Total VA rating: 30VA
 Insulation: Class E (120 °C)
 Magnetising current: <65mA
 Temperature rise: <60 °C
 Regulation: ≈10%
 External AC fuse (required): 500mA
 Thermal fuse: 125 °C
 Weight: ≈1kg
 Primary connection: 200mm fly leads
 Secondary connection: Solder tags

Must be used with a standard 500mA external AC fuse.

Price Each	RRP	4+	10+
M 2156L	21.50	19.35	17.20

9V - 24V Multi-Tapped 6.6A Max



Primary voltage: 240V AC
 Total VA rating: 60VA
 Insulation: Class E (120 °C)
 Magnetising current: <85mA
 Temperature rise: <65 °C
 Regulation: ≈10%
 External AC fuse (required): 500mA
 Thermal fuse: 125 °C
 Weight: ≈1.4kg
 Primary connection: 200mm fly leads
 Secondary connection: Solder tags



Must be used with a 500mA external AC fuse.
 *Maximum current when connected in parallel

Secondary voltages available:

Voltage	Current AC
9V	6.6A*
12V	5A*
15V	2.5A
18V	2.5A
21V	2.5A
24V	2.5A

Price Each	RRP	4+	10+
M 2165L	30.50	28.00	25.95

24V Single Winding 3A Max





Primary voltage: 240V AC
 Total VA rating: 72VA
 Insulation: Class E (120 °C)
 Magnetising current: <85mA
 Temperature rise: <65 °C
 Regulation: ≈10%
 External AC fuse (required): 500mA
 Thermal fuse: 125 °C
 Weight: ≈1.4kg
 Primary connection: 200mm fly leads
 Secondary connection: 200mm fly leads

Must be used with a standard 500mA external AC fuse.

Price Each	RRP	4+	10+
M 2158L	31.50	28.35	25.95

24V Single Winding 5A Max






Primary voltage: 240V AC
 Total VA rating: 120VA
 Insulation: Class E (120 °C)
 Magnetising current: <85mA
 Temperature rise: <65 °C
 Regulation: ≈10%
 External AC fuse (required): 500mA
 Thermal fuse: 115 °C
 Weight: ≈2.2kg
 Primary connection: 200mm fly leads
 Secondary connection: Solder tags

Must be used with a standard 500mA external AC fuse.

Price Each	RRP	4+	10+
M 2190L	53.95	48.75	43.25

12V - 30V Multi-Tapped 6A Max



Primary Voltage: 240V AC
 Total VA Rating: 100VA
 Insulation: Class E (120 °C)
 Magnetising Current: <85mA
 Temperature Rise: <70 °C
 Regulation: ≈14%
 External AC fuse (required): 500mA
 Thermal fuse: 125 °C
 Weight: ≈1.6kg
 Primary connection: 200mm fly leads
 Secondary connection: Solder tags

Must be used with a 500mA external AC fuse.

*Maximum current when connected in parallel

Secondary Voltages Available:

Voltage	Current AC
12V	6.6A*
15V	6.6A*
24V	3.3A
27V	3.3A
30V	3.3A

Price Each	RRP	4+	10+
M 2170L	38.95	35.00	31.25

All currents listed are AC. For DC circuit information see the data at the front of this section. Manufacturers please note, we recommend that a sample is obtained to confirm suitability. Specifications may change without notice.