


▼ Capacitors

Polyester MKT Style Capacitors


- Constant lead spacing
- Tolerance: ±5%
- 5.08mm pitch
- "A" models 63V DC rated.
- "B" models 100V DC rated.
- Bulk quantities on bandolier tape.



Price Each	Value	EIA Code	L	W	H	RRP	10+	100+
R 3001B	0.001µF	102	7.2	2.5	6.5	0.35	0.25	0.20
R 3002B	0.0012µF	122	7.2	2.5	6.5	0.35	0.25	0.20
R 3003B	0.0015µF	152	7.2	2.5	6.5	0.35	0.25	0.20
R 3005B	0.0022µF	222	7.2	2.5	6.5	0.35	0.25	0.20
R 3007B	0.0033µF	332	7.2	2.5	6.5	0.35	0.25	0.20
R 3009B	0.0047µF	472	7.2	2.5	6.5	0.35	0.25	0.20
R 3010B	0.0056µF	562	7.2	2.5	6.5	0.35	0.25	0.20
R 3011B	0.0068µF	682	7.2	2.5	6.5	0.35	0.25	0.20
R 3012B	0.0082µF	882	7.2	2.5	6.5	0.35	0.25	0.20
R 3013B	0.01µF	103	7.2	2.5	6.5	0.35	0.25	0.20
R 3014B	0.012µF	123	7.2	2.5	6.5	0.35	0.25	0.20
R 3015B	0.015µF	153	7.2	2.5	6.5	0.35	0.25	0.20
R 3016A	0.018µF	183	7.2	2.5	6.5	0.30	0.25	0.20
R 3017B	0.022µF	223	7.2	2.5	6.5	0.35	0.25	0.20
R 3019B	0.033µF	333	7.2	2.5	6.5	0.35	0.25	0.20
R 3021B	0.047µF	473	7.2	2.5	6.5	0.35	0.25	0.20
R 3023B	0.068µF	683	7.2	2.5	6.5	0.35	0.25	0.20
R 3025B	0.1µF	104	7.2	2.5	6.5	0.40	0.27	0.23
R 3027B	0.15µF	154	7.2	3.5	7.5	0.45	0.30	0.24
R 3029B	0.22µF	224	7.2	3.5	7.5	0.45	0.30	0.24
R 3031B	0.33µF	334	7.2	4.5	9.5	0.65	0.45	0.36
R 3032B	0.39µF	394	7.2	4.5	9.5	0.65	0.45	0.36
R 3033B	0.47µF	474	7.2	5.0	10.0	0.65	0.45	0.36
R 3035B	0.68µF	684	7.2	6.0	11.0	0.85	0.57	0.49
R 3037B	1.0µF	105	7.2	6.0	11.0	0.95	0.65	0.54

Tantalum Capacitors

- Polarised, high capacitance for their size.
- Good temperature/age stability.
- Resin dipped encapsulated package.
- 5mm pitch.
- Tolerance: ±10%
- Bulk quantities supplied on bandolier tape.



Price Each	Value	EIA Code	Volts DC	Pitch	RRP	10+	100+
R 2620A	0.1µF	104	35V	5	0.75	0.55	0.45
R 2622A	0.22µF	224	35V	5	0.75	0.55	0.45
R 2624A	0.33µF	334	35V	5	0.75	0.55	0.45
R 2626	0.47µF	474	35V	5	0.75	0.55	0.45
R 2628A	1µF	105	35V	5	0.75	0.55	0.45
R 2632A	2.2µF	225	35V	5	0.90	0.70	0.65
R 2634A	3.3µF	335	25V	5	0.95	0.65	0.55
R 2635A	4.7µF	475	25V	5	0.95	0.65	0.55
R 2636A	6.8µF	685	25V	5	1.15	0.80	0.65
R 2638A	10µF	106	25V	5	1.15	0.80	0.65
R 2642A	22µF	226	16V	5	1.20	1.00	0.85

50V DC Rated Monolithic Capacitors


- High capacitance for their size
- Resin encapsulated.
- X7R -55°C to 125°C ±15°C
- Y5V -30°C to 85°C, +22°C, -82°C
- Bulk quantities supplied on bandolier tape.



Price Each	Value	EIA Code	Type	Volts DC	Pitch	RRP	10+	100+
R 2900A	0.001µF	102	X7R	50V	5	0.35	0.25	0.21
R 2905A	0.0022µF	222	X7R	50V	5	0.35	0.25	0.21
R 2910A	0.01µF	103	X7R	50V	5	0.35	0.25	0.21
R 2915A	0.022µF	223	Y5V	50V	5	0.35	0.25	0.21
R 2920	0.033µF	333	Y5V	50V	5	0.35	0.25	0.21
R 2925A	0.047µF	473	Y5V	50V	5	0.35	0.25	0.21
R 2930A	0.1µF	104	Y5V	50V	5	0.35	0.25	0.21
R 2931	0.1µF	104	X7R	50V	5	0.35	0.25	0.21
R 2935A	0.22µF	224	Y5V	50V	5	0.35	0.25	0.21
R 2945A	0.47µF	474	Y5V	50V	5	0.75	0.53	0.45
R 2950A	1µF	105	Y5V	50V	5	0.75	0.53	0.45
R 2964	2.2µF	225	X7R	50V	5	0.95	0.85	0.75

Metallised and Mylar Polyester Capacitors (Greencaps)

- Non-inductive
- High temperature stability
- Ideal for coupling & bypass applications
- Tolerance ±5%
- Temperature rating -40°C to +85°C
- All quantities are supplied loose.




Price Each	Value	EIA Code	Type	Volts DC	Pitch	RRP	10+	100+
R 2700B	0.001µF	102	Mylar	100V	3.5	0.30	0.21	0.17
R 2701	0.0012µF	122	Metal	100V	3.5	0.30	0.21	0.17
R 2702B	0.0015µF	152	Mylar	100V	3.5	0.30	0.21	0.17
R 2703B	0.0018µF	182	Metal	100V	3.5	0.30	0.21	0.17
R 2704B	0.0022µF	222	Metal	100V	3.5	0.30	0.21	0.17
R 2705B	0.0027µF	272	Mylar	100V	3.5	0.30	0.21	0.17
R 2706B	0.0033µF	332	Mylar	100V	3.5	0.30	0.21	0.17
R 2708B	0.0039µF	392	Metal	100V	4	0.30	0.21	0.17
R 2710B	0.0047µF	472	Mylar	100V	3.5	0.30	0.21	0.17
R 2712B	0.0056µF	562	Metal	100V	3.5	0.30	0.21	0.17
R 2714A	0.0068µF	682	Metal	100V	3.5	0.30	0.21	0.17
R 2716B	0.0082µF	822	Metal	100V	4.0	0.30	0.21	0.17
R 2718B	0.01µF	103	Mylar	100V	4.5	0.30	0.21	0.17
R 2719A	0.012µF	123	Metal	100V	4.5	0.30	0.21	0.17
R 2720A	0.015µF	153	Metal	100V	4.5	0.30	0.21	0.17
R 2721B	0.018µF	183	Metal	100V	4.5	0.30	0.21	0.17
R 2722D	0.022µF	223	Mylar	100V	4.5	0.30	0.21	0.17
R 2723B	0.027µF	273	Mylar	100V	5.5	0.30	0.21	0.17
R 2724	0.033µF	333	Metal	100V	5.0	0.30	0.21	0.17
R 2726A	0.039µF	393	Metal	100V	5.0	0.30	0.21	0.17
R 2728A	0.047µF	473	Metal	100V	6.0	0.30	0.21	0.17
R 2730A	0.056µF	563	Metal	100V	6.0	0.30	0.21	0.17
R 2732B	0.068µF	683	Metal	100V	6.5	0.30	0.21	0.17
R 2734C	0.082µF	823	Mylar	100V	7.5	0.30	0.21	0.17
R 2736B	0.1µF	104	Mylar	100V	7.0	0.30	0.21	0.17
R 2737B	0.12µF	124	Metal	100V	7.5	0.30	0.21	0.17
R 2738B	0.15µF	154	Mylar	100V	10	0.30	0.21	0.17
R 2739B	0.18µF	184	Metal	100V	10	0.30	0.21	0.17
R 2740B	0.22µF	224	Mylar	100V	10	0.30	0.21	0.17
R 2742	0.27µF	274	Metal	100V	10	0.42	0.29	0.25
R 2743B	0.33µF	334	Metal	100V	10	0.42	0.29	0.25
R 2744C	0.33µF	334	Metal	250V	15	0.65	0.55	0.35
R 2746C	0.47µF	474	Metal	250V	15	0.90	0.75	0.60
R 2748C	1.0µF	105	Metal	250V	20	2.25	1.55	1.35
R 2750A	2.2µF	225	Metal	250V	26	3.45	2.35	2.00
R 2770C	0.01µF	103	Metal	630V	10	0.60	0.42	0.36
R 2772C	0.022µF	223	Metal	630V	11	0.80	0.56	0.48
R 2776C	0.047µF	473	Metal	630V	15	0.95	0.65	0.55
R 2778C	0.1µF	104	Metal	630V	15	1.40	0.95	0.80
R 2780B	0.22µF	224	Metal	630V	20.5	1.40	0.95	0.80
R 2784C	0.47µF	474	Metal	630V	22.5	1.95	1.35	1.15

Class X2 240V AC Mains Capacitors

Class X2 suppression capacitors are designed for direct connection across the 240V mains supply between current carrying conductors.

- Tolerance: ±10%.
- All quantities are supplied loose.
- Approvals: ENEC, VDE, TUV, CE, UL, CUL.



Price Each	Value	EIA Code	Volts AC	Pitch	RRP	10+	25+
R 3102A	0.01µF	103	275V	10	0.95	0.65	0.55
R 3107A	0.022µF	223	275V	10	0.95	0.65	0.55
R 3112A	0.033µF	333	275V	10	0.95	0.65	0.55
R 3117A	0.047µF	473	275V	15	0.95	0.65	0.55
R 3122A	0.1µF	104	275V	15	1.25	0.85	0.75
R 3127A	0.22µF	224	275V	22.5	1.35	0.90	0.80
R 3129A	0.33µF	334	275V	22.5	2.50	1.90	1.20
R 3132A	0.47µF	474	275V	22.5	3.75	2.60	2.20
R 3134A	0.68µF	684	275V	27.5	3.95	2.75	2.40
R 3137A	1µF	105	275V	27.5	4.25	2.90	2.45

Education & Government 30 Day Accounts

Universities, Colleges, Secondary Schools, TAFE Colleges & Government Departments qualify for 30 day credit accounts. For more information call your local store.