

▼ Capacitors

**Lelon® Low ESR Electrolytic Capacitors (105°C Rated)**



10V Series

ROHS

- Tolerance ± 20%
- Rated life 2000-5000hrs
- All quantities are supplied loose.

Price Each	Value	Volts DC	Ripple (mA)	Diameter	Pitch	Height	RRP	10+	100+
R 6067	10µF	50V	68	5	2	11	0.25	0.20	0.12
R 6077	22µF	50V	143	6.3	2.5	11	0.30	0.24	0.14
R 6084	33µF	25V	108	5	2	11	0.50	0.35	0.20
R 6233	47µF	10V	78	5	2	11	2.40	1.95	1.75
R 6104	47µF	25V	182	6.3	2.5	11	0.50	0.35	0.20
R 6107	47µF	50V	320	8	3.5	11.5	0.50	0.35	0.20
R 6234	100µF	10V	182	6.3	2.5	11	2.40	1.95	1.75
R 6124	100µF	25V	320	8	3.5	11.5	0.60	0.45	0.30
R 6127	100µF	50V	445	10	5	16	0.70	0.60	0.40
R 6235	220µF	10V	280	8	3.5	11.5	2.40	1.95	1.75
R 6144	220µF	25V	360	10	5	12.5	0.65	0.55	0.35
R 6147	220µF	50V	825	10	5	25	0.80	0.75	0.50
R 6236	470µF	10V	410	10	5	12.5	2.40	1.95	1.75
R 6164	470µF	25V	775	10	5	20	0.80	0.75	0.50
R 6167	470µF	50V	1085	13	5	25	1.40	1.20	0.85
R 6237	1000µF	10V	690	10	5	20	2.40	1.95	1.75
R 6184	1000µF	25V	1080	13	5	25	2.40	2.15	1.90
R 6187	1000µF	50V	1595	16	7.5	32	2.00	1.65	1.35
R 6238	2200µF	10V	1200	12.5	5	25	2.40	1.95	1.75
R 6204	2200µF	25V	1595	16	7.5	25	1.65	1.35	1.00
R 6207	2200µF	50V	2465	18	7.5	40	4.15	3.80	2.95
R 6205	3300µF	25V	2065	18	7.5	35.5	2.40	1.95	1.75
R 6239	3300µF	10V	1200	12.5	5	25	2.40	1.95	1.75
R 6208	3300µF	50V	2685	18	7.5	35.5	2.40	1.95	1.75
R 6224	4700µF	25V	2465	18	7.5	40	2.40	1.95	1.75

**Lelon® Electrolytic Capacitors (105°C Rated)**



ROHS

- "RT" parts supplied in tape format for manufacturers.
- Tolerance ±20%,
- Temp range -40° to +105°C.
- Rated life 2000hrs
- Sleeve colour may vary (green or black)

Price Each	Value	Volts DC	Surge DC	Ripple (mA)	Diameter	Pitch	Height	Tape Version	Reel Qty	RRP	10+	100+
R 4710	0.47µF	63V	79V	9	5	2	11	RT4710	1200	0.25	0.20	0.12
R 4718	1µF	63V	79V	15	5	2	11	RT4718	1200	0.25	0.20	0.12
R 4728	2.2µF	63V	79V	30	5	2	11	RT4728A	2000	0.25	0.20	0.12
R 4738	3.3µF	63V	79V	31	5	2	11	RT4738	1200	0.25	0.20	0.12
R 4748	4.7µF	63V	79V	36	5	2	11	RT4748A	1200	0.25	0.20	0.12
R 4767	10µF	50V	63V	50	5	2	11	RT4767A	1200	0.25	0.20	0.12
R 4768	10µF	63V	79V	54	5	2	11	RT4768A	2000	0.25	0.20	0.12
R 4787	22µF	50V	63V	78	5	2	11	RT4787A	2000	0.50	0.40	0.25
R 4797	33µF	50V	63V	90	5	2	11	RT4797A	1200	0.40	0.32	0.19
R 4805	47µF	35V	44V	90	5	2	11	RT4805A	1200	0.40	0.32	0.19
R 4807	47µF	50V	63V	120	6.3	2.5	11	RT4807A	1000	0.70	0.55	0.35
R 4808	47µF	63V	79V	130	6.3	2.5	11	RT4808	1000	0.40	0.32	0.19
R 4825	100µF	35V	44V	150	6.3	2.5	11	RT4825A	2000	0.60	0.47	0.28
R 4827	100µF	50V	63V	188	8	3.5	11.5	RT4827A	800	0.65	0.51	0.31
R 4828	100µF	63V	79V	235	10	5	12.5	RT4828	500	0.75	0.59	0.35
R 4847	220µF	50V	63V	300	10	5	16	RT4847	500	0.80	0.63	0.38
R 4848	220µF	63V	79V	335	10	5	16	RT4848	500	0.90	0.71	0.43
R 4857	330µF	50V	63V	410	10	5	16	RT4857	500	0.90	0.71	0.43
R 4858	330µF	63V	79V	510	10	5	20	RT4858	500	0.95	0.75	0.45
R 4865	470µF	35V	44V	460	10	5	16	RT4865	500	1.00	0.79	0.47
R 4867	470µF	50V	63V	530	10	5	20	RT4867	500	1.30	1.02	0.61
R 4868	470µF	63V	79V	640	12.5	5	20	-	-	1.50	1.18	0.71
-	1000µF	25V	-	-	-	-	-	RT4884A	500	-	-	-
R 4885	1000µF	35V	44V	810	12.5	5	20	RT4885A	300	1.40	1.10	0.60
R 4887	1000µF	50V	63V	950	12.5	5	25	RT4887A	200	1.60	1.26	0.76
R 4906	2200µF	50V	63V	1470	16	7.5	35.5	-	-	2.90	2.28	1.37
R 4913	3300µF	25V	32V	1440	16	12.5	25	-	-	1.95	1.54	0.92
R 4914	3300µF	35V	44V	1610	16	7.5	35.5	-	-	1.95	1.54	0.92
R 4917	3300µF	50V	63V	1770	18	7.5	35.5	-	-	4.70	3.70	2.22
R 4922	4700µF	35V	44V	1900	18	7.5	35.5	-	-	1.70	1.40	1.00
R 4926	4700µF	50V	63V	2340	22	10	40	-	-	4.95	3.90	2.34

**Lelon® PCB Mount Electrolytic Capacitors With "Snap In" Terminals (85°C Rated)**

- Snap-in PCB mount type.
- 400V DC models are used primarily in power supply designs.
- Tolerance ±20%
- Temperature range -40° to +85°C.
- Rated life 2000hrs.
- All quantities are supplied loose.



ROHS

Price Each	Value	Volts DC	Ripple (mA)	Diameter	Pitch	Height	RRP	10+	25+
R 5368	100µF	400V	710	22	10	30	4.500	3.90	3.50
R 5408	220µF	400V	1150	25	10	40	6.95	6.30	5.60
R 5428	330µF	400V	1460	25	10	50	9.90	9.50	6.95
R 5448	470µF	400V	1990	30	10	50	12.95	11.95	9.05
R 5465	680µF	200V	2300	30	10	30	7.95	6.90	5.90
R 5541	3300µF	50V	2380	25	10	25	5.50	5.20	3.85
R 5563	4700µF	100V	5130	30	10	50	9.90	9.50	6.95
R 5573	5600µF	100V	5750	35	10	45	11.50	10.50	9.00
R 5581	6800µF	50V	3850	30	10	35	6.50	5.95	4.95
R 5590	8200µF	16V	2560	22	10	25	5.50	5.20	3.85
R 5601	10000µF	50V	5020	30	10	40	6.95	6.30	5.60