

▼ Capacitors

**Lelon® Electrolytic Capacitors (85°C Rated)**



ROHS

- Low impedance
- Case sizes are smaller than conventional general purpose capacitors, with very high performance.
- Can sizes larger than 8mm diameter have safety vents or rubber bung.
- Temp range -40° to +85°C
- Tolerance: ±20%
- Rated life: 2000-3000hrs
- **All quantities supplied loose.**

Please Note: Due to continued product development, specifications are subject to change without notice.

Price Each	Value	Volts DC	Surge DC	Ripple (mA)	Diameter	Pitch	Height	RRP	10+	100+
R 5010	0.47µF	63V	79V	9.5	5	2	11	0.25	0.20	0.12
R 5018	1µF	63V	79V	17	5	2	11	0.30	0.25	0.15
R 5028	2.2µF	63V	79V	28	5	2	11	0.30	0.25	0.15
R 5038	3.3µF	63V	79V	34	5	2	11	0.30	0.25	0.15
R 5048	4.7µF	63V	79V	45	5	2	11	0.30	0.25	0.15
R 5065	10µF	35V	44V	58	5	2	11	0.30	0.25	0.15
R 5067	10µF	50V	63V	65	5	2	11	0.30	0.25	0.15
R 5068	10µF	63V	79V	70	5	2	11	0.30	0.25	0.15
R 5084	22µF	25V	32V	80	5	2	11	0.30	0.25	0.15
R 5087	22µF	50V	63V	95	5	2	11	0.35	0.30	0.20
R 5088	22µF	63V	79V	115	6.3	2.5	11	0.95	0.75	0.45
R 5094	33µF	25V	32V	97	5	2	11	0.40	0.35	0.20
R 5097	33µF	50V	63V	125	5	2	11	0.50	0.35	0.25
R 5098	33µF	63V	79V	150	8	3.5	11.5	0.50	0.35	0.25
R 5102	47µF	16V	20V	110	5	2	11	0.50	0.35	0.25
R 5104	47µF	25V	32V	115	5	2	11	0.50	0.35	0.25
R 5105	47µF	35V	44V	130	5	2	11	0.50	0.35	0.25
R 5107	47µF	50V	63V	165	6.3	2.5	11	0.50	0.35	0.25
R 5108	47µF	63V	79V	190	8	3.5	11.5	0.50	0.35	0.25
R 5123	100µF	16V	20V	165	5	2	11	0.50	0.35	0.25
R 5124	100µF	25V	32V	190	6.3	2.5	11	0.55	0.40	0.30
R 5125	100µF	35V	44V	240	8	3.5	11.5	0.70	0.55	0.35
R 5127	100µF	50V	63V	260	8	3.5	11.5	0.75	0.60	0.40
R 5128	100µF	63V	79V	320	10	5	12.5	1.00	0.80	0.60
R 5143	220µF	16V	20V	300	8	3.5	11.5	0.40	0.35	0.20
R 5144	220µF	25V	32V	320	8	3.5	11.5	0.70	0.55	0.35
R 5147	220µF	50V	63V	455	10	5	12.5	0.95	0.70	0.50
R 5148	220µF	63V	79V	490	10	5	16	1.10	0.80	0.55
R 5153	330µF	25V	32V	440	8	3.5	11.5	0.75	0.60	0.40
R 5157	330µF	50V	63V	585	10	5	16	1.10	0.80	0.55
R 5158	330µF	63V	79V	710	10	5	20	1.10	0.90	0.60
R 5163	470µF	16V	20V	440	8	3.5	11.5	0.70	0.55	0.35
R 5164	470µF	25V	32V	545	10	5	12.5	0.80	0.65	0.40
R 5165	470µF	35V	44V	740	10	5	16	1.15	0.95	0.65
R 5167	470µF	50V	63V	755	10	5	20	1.50	1.15	0.70
R 5168	470µF	63V	79V	1050	16	7.5	25	1.70	1.40	0.80
R 5182	1000µF	16V	20V	785	10	5	16	1.10	0.80	0.60
R 5183	1000µF	25V	32V	955	10	5	20	1.25	1.05	0.65
R 5185	1000µF	35V	44V	1145	13	5	20	1.60	1.25	0.75
R 5187	1000µF	50V	63V	1530	16	7.5	25	1.85	1.45	0.90
R 5188	1000µF	63V	79V	1700	16	7.5	31.5	2.25	1.80	1.05
R 5202	2200µF	16V	20V	1295	13	5	20	1.10	0.90	0.60
R 5205	2200µF	25V	32V	1540	13	5	25	1.60	1.25	0.75
R 5206	2200µF	50V	63V	2231	18	7.5	40	3.35	2.65	1.60
R 5208	2200µF	63V	79V	2385	22	10	40	4.70	3.70	2.20
R 5214	3300µF	25V	32V	1975	16	7.5	25	2.25	1.80	1.05
R 5217	3300µF	50V	63V	2500	18	7.5	35.5	5.40	4.25	2.55
R 5222	4700µF	16V	20V	2260	16	7.5	31.5	1.85	1.45	0.90
R 5224	4700µF	25V	32V	2520	16	7.5	31.5	3.15	2.45	1.50
R 5226	4700µF	50V	63V	3155	22	10	40	5.70	4.50	2.65
R 5228	4700µF	63V	79V	3560	25	12.5	50	6.80	5.65	4.25
R 5234	10000µF	25V	32V	3440	22	10	40	6.30	5.20	3.80

**Motor Start Capacitors**



Can type

Block type

ROHS

- Low dissipation factor • High insulation resistance • -40°C to 85°C operating temperature • Tolerance 5% • Ideal for single phase induction motors. Please Note: Due to continued product development, specifications are subject to change without notice.


Price Each	Value	Volts (AC)	Type	Dimensions	RRP	5+	10+
R 5607	3µF	400V	Can	400 x 65H	19.50	13.50	11.50
R 5625	5µF	400V	Can	400 x 55H	19.50	13.50	11.50
R 5610A	6µF	400V	Can	400 x 55H	19.50	13.50	11.50
R 5613A	20µF	400V	Can	450 x 75H	19.50	13.50	11.50
R 5616A	30µF	400V	Can	500 x 75H	19.50	13.50	11.50
R 5618	40µF	400V	Can	400 x 115H	19.50	13.50	11.50
R 5619	10µF	400V	Block	58L x 34W x 23D	19.50	13.50	11.50
R 5621	12µF	400V	Block	48L x 40W x 28D	19.50	13.50	11.50

**Trimmer Capacitors**



Working voltage: 250V DC  
 Withstand voltage: 550V DC  
 Insulation resistance: 10GΩ min at 250V DC  
 Operating temperature: -55°C to +85°C  
 Q value: >1000 at 1MHz at max setting

R 4001	1.8 to 7pF	Red
R 4005	3.5 to 20pF	Blue
R 4007	5 to 30pF	Yellow
R 4009	8.5 to 40pF	Brown
R 4011	8.5 to 50pF	Green
R 4013	8.5 to 70pF	Black



Price Each	RRP	10+	25+
ALL	2.00	1.90	1.45

**Order online 24/7, 365 days a year!**

Easy online ordering at [www.altronics.com.au](http://www.altronics.com.au)