

▼ Figure 8 Hook Up Cable

Double Insulated Heavy Duty 14/0.30



ROHS

Ideal for running power in automotive applications. Double sheath for added protection.

Size:	2 x 14/0.30
Voltage rating:	300V AC @ 10A
Dimensions:	≈3.8 x 6.2mm
Conductor:	1.0mm ² (≈17AWG)
Jacket material:	PVC
Resistance:	0.00445Ω/m @ 20°C
Temperature rating:	75°C

Price Per	RRP (m)	Roll
W 4146 100m Roll	1.95	150.00
W 4148 300m Roll	1.95	450.00
W 4166 100m Roll Tinned	2.25	180.00

Double Insulated Heavy Duty 28/0.30



ROHS

Ideal for running power in automotive applications. Double sheath for added protection.

Size:	2 x 28/0.30
Voltage rating:	300V AC @ 12A
Dimensions:	≈4.0 x 7.0mm
Conductor:	2.0mm ² (≈14AWG)
Jacket material:	PVC
Resistance:	0.0093Ω/m @ 20°C
Temperature rating:	75°C

Price Per	RRP (m)	Roll
W 4150 100m Roll	2.95	220.00
W 4152 300m Roll	2.95	660.00
W 4170 100m Roll Tinned	2.95	235.00

Double Insulated Heavy Duty 56/0.30



ROHS

Huge 20A current rating. Double sheath for added protection.

Size:	2 x 56/0.30
Voltage rating:	300V AC @ 20A
Dimensions:	≈5.6 x 9.2mm
Conductor:	4.0mm ² (≈12AWG)
Jacket material:	PVC
Resistance:	0.0047Ω/m @ 20°C
Temperature rating:	75°C

Price Per	RRP (m)	Roll
W 4154 100m Roll	4.95	380.00

Double Insulated Heavy Duty 85/0.30



ROHS

For high current auto and marine power. Double sheath for added protection.

Size:	2 x 85/0.30
Voltage rating:	300V AC @ 28A
Dimensions:	≈6.4 x 10.8mm
Conductor:	6.0mm ² (≈10AWG)
Jacket material:	PVC
Resistance:	0.0031Ω/m @ 20°C
Temperature rating:	75°C

Price Per	RRP (m)	Roll
W 4158 100m Roll	7.95	600.00

Double Insulated Heavy Duty 112/0.30



ROHS

new for 2019

For high current auto and marine power. Double sheath for added protection.

Size:	2 x 112/0.30
Voltage rating:	300V AC @ 80A
Dimensions:	≈7.6 x 13.2mm
Conductor:	8.0mm ² (≈8AWG)
Jacket material:	PVC
Resistance:	0.0031Ω/m @ 20°C
Temperature rating:	75°C

Price Per	RRP (m)	Roll
W 4162 100m Roll	11.50	895.00

▼ Speaker Cable

Flat Cable Oxygen Free 96/0.1



W 2980


ROHS

This low profile 18AWG cable allows running of speaker wiring under carpet and rugs.

Size:	2 x 96/0.1
Dimensions:	≈2.5 x 12.5mm
Conductor:	0.75mm ² (≈18AWG)
Jacket material:	PVC
Resistance:	0.016Ω/m @ 20°C
Temperature rating:	90°C

Price Per	RRP (m)	Roll
W 2980 50m Roll	2.95	97.50
W 2981 100m Roll	2.95	185.00

“Whopper” Cable Oxygen Free 102/0.12



W 2140


ROHS

Our most popular choice for home hi-fi and theatre use. Translucent outer sheath with blue trace.

Size:	2 x 102/0.12
Dimensions:	≈4.0 x 8.3mm
Conductor:	1.15mm ² (≈17AWG)
Jacket material:	PVC
Resistance:	0.016Ω/m @ 20°C
Temperature rating:	90°C

Price Per	RRP (m)	Roll
W 2140 50m Roll	2.00	72.50
W 2141 100m Roll	2.00	145.00

“Whopper” Cable Low Loss 90/0.18



W 2130

ROHS

A 14AWG cable for speaker connection cable featuring translucent outer sheath.

Size:	2 x 90/0.18
Dimensions:	≈4.0 x 8.3mm
Conductor:	2.29mm ² (≈14AWG)
Jacket material:	PVC
Resistance:	0.0081WΩ/m @ 20°C
Temperature rating:	90°C

Price Per	RRP (m)	Roll
W 2130 50m Roll	3.65	117.50
W 2132 100m Roll	3.65	235.00

“Whopper” Cable Oxygen Free 315/0.12



W 2145

ROHS

A no compromises 12AWG high power hi-fi speaker cable with durable translucent outer sheath.

Size:	2 x 315/0.12
Dimensions:	≈6.0 x 12mm
Conductor:	3.56mm ² (≈12AWG)
Jacket material:	PVC
Resistance:	0.0052Ω/m @ 20°C
Temperature rating:	90°C


Price Per	RRP (m)	Roll
W 2145 50m Roll	5.95	200.00
W 2146 100m Roll	5.95	400.00

Pro Speaker Cable



ROHS

Double insulated with soft sheath.



Size:	24/0.20	32/0.20
Rating:	240V AC @ 7.5A	240V AC @ 7.5A
Outside diameter:	≈6mm	≈6.9mm
Conductor:	0.75mm ² (18AWG)	1mm ² (17AWG)
Resistance:	0.0245Ω/m	0.00445Ω/m
Temperature rating:	90°C	90°C


Price Per	1 Roll	2 Rolls
W 2193 24/0.20 50m Roll	1.80	75.00
W 2192 24/0.20 200m Roll	1.80	260.00
W 2194 32/0.20 50m Roll	1.95	87.50
W 2195 32/0.20 200m Roll	1.95	350.00

4 Core Install Cable



ROHS

Designed for installing a pairs of speakers over a single cable run. Metre marked.



Size:	4 x 54/0.14	65/0.14
Rating:	300V AC @ 7.4A	300V AC @ 10A
Outside diameter:	≈8mm	≈8.3mm
Conductor:	0.83mm ² (18AWG)	1mm ² (17AWG)
Resistance:	0.0222Ω/m	0.0185Ω/m
Temperature rating:	90°C	90°C

Price Per	RRP (m)	Roll
W 3121 54/0.14 100m Roll	3.40	235.00
W 3122 54/0.14 200m Roll	3.40	470.00
W 3125 65/0.14 100m Roll	3.90	255.00
W 3126 65/0.14 200m Roll	3.90	510.00

PDF Downloads

Should you require any additional information on the operation or features of our products, you can find brochures, instructions and information in PDF format online at altronics.com.au.