


▼ Power Cable

3 Core Mains Flex


Suitable for mains extension leads.



	W 0572	W 0574	W 0576
Size:	3x24/0.20	3x32/0.20	3x30/0.25
Rating (240V AC):	7.5A	10A	15A
Outside diameter:	6.8mm	7.1mm	8.3mm
Conductor gauge:	≈18AWG	≈17AWG	≈16AWG
Conductor area:	0.75mm <sup>2</sup>	1mm <sup>2</sup>	1.5mm <sup>2</sup>

Price Per		RRP (m)	Roll
W 0572	7.5A Black 100m Roll	2.25	190.00
W 0574	10A Black 100m Roll	2.95	225.00
W 0576	15A Black 100m Roll	3.50	295.00

3 Core TPS Building Wire



	W 0587	W 0588
Voltage rating:	240V AC	240V AC
Current rating:	15A	20A
Conductor size:	1.5mm <sup>2</sup> / 16AWG	2.5mm <sup>2</sup> / 13AWG
Dimensions:	≈9.7 x 4.4mm	≈12.1 x 5.3mm

Price Per		RRP (m)	Roll
W 0587	Lighting 15A 100m	2.00	180.00
W 0588	Power 20A 100m	2.95	250.00

Power Cable OFC 61A 630/0.12

ROHS



	W 4100 Red	W 4102 Black
Size:	1 x 630/0.12	
Rating:	300V AC @ 61A	
Outside diameter:	≈6.3mm	
Conductor:	7.1mm <sup>2</sup> (≈8AWG)	
Resistance:	0.00226Ω/m	
Temperature rating:	105°C	

Price Per		RRP (m)	Roll
50m Roll		4.95	195.00

Power Cable 90A 119/0.30

ROHS



	W 4216A Red	W 4218A Black
Size:	119/0.30	
Max current rating:	90A	
Outside diameter:	≈6mm	
Conductor:	8.4mm <sup>2</sup> (≈8AWG)	
Resistance:	0.00206Ω/m	
Temperature rating:	90°C	

Price Per	RRP (m)	10+ (m)	Roll
30m Roll	5.95	4.95	135.00

Power Cable OFC 110A 1666/0.12

ROHS



	W 4200 Red	W 4202 Black
Size:	1666/0.12	
Voltage rating:	300V AC @ 110A	
Outside diameter:	≈10.2mm	
Conductor area:	18.8mm <sup>2</sup> (≈4AWG)	
Resistance:	0.000815Ω/m	
Temperature rating:	105°C	

Price Per	RRP (m)	Roll
50m Roll	9.90	395.00

Power Cable 160A 287/0.30

ROHS



High current capacity suitable for between battery banks & inverters. Suits H 1763A/H 1765A lugs.

	W 4206A Red	W 4208A Black
Size:	287/0.30	
Max current rating:	160A	
Outside diameter:	≈8.15mm	
Conductor:	20.25mm <sup>2</sup> (≈4AWG)	
Resistance:	0.00022Ω/m	
Temperature rating:	90°C	

Price Per	RRP (m)	10+ (m)	Roll
30m Roll	11.95	10.90	297.00

Power Cable 210A 456/0.30

ROHS



High current capacity suitable for between battery banks & inverters. Suits H 1768A/H 1769A lugs.

	W 4211A Red	W 4213A Black
Size:	456/0.30	
Max current rating:	210A	
Outside diameter:	≈11mm	
Conductor:	32.2mm <sup>2</sup> (≈2AWG)	
Resistance:	0.000513Ω/m	
Temperature rating:	90°C	

Price Per	RRP (m)	10+ (m)	Roll
30m Roll	13.95	12.95	357.00

Power Cable OFC 250A 2842/0.15

ROHS



Solid copper 0 gauge high current power cabling for battery banks. Suits H 1776A/H 1777A lugs.


	W 4190A Red	W 4191A Black
Size:	2842/0.15	
Max current rating:	250A	
Outside diameter:	≈15.5mm	
Conductor:	50mm <sup>2</sup> (≈1/0AWG)	
Resistance:	0.000322Ω/m	
Temperature rating:	70°C	

Price Per	RRP (m)	Roll	2 Rolls
30m Roll	21.95	585.00	495.00

▼ Trailer Lighting Cable

Multi-Core Trailer Cable

Suitable for trailer wiring to lights and indicators. UV stabilised sheath with high weather resistance.




Model	W 4220	W 4222
Size:	5 x 7/0.32	7 x 9/0.30
Rating:	4A	6A
Outside diameter:	5.8mmØ	7.4mmØ
Conductor:	0.56mm <sup>2</sup> (20AWG)	0.65mm <sup>2</sup> (19AWG)

Price Per	RRP (m)	10+ (m)	Roll	
W 4220	5 core 100m	2.95	2.50	200.00
W 4222	7 core 100m	4.75	4.25	375.00

▼ Alarm / Security Cable

4 Core Security

305m lengths supplied in pull boxes. Other models supplied on reels.





	7/0.20	14/0.20
Current rating:	2.2A	4.5A
Conductors:	4 x 7/0.20	4 x 14/0.20
Outside diameter:	≈3.5mm	≈4.6mm
Resistance @ 20°C:	0.084Ω/m	0.042Ω/m
Conductor area:	0.22mm <sup>2</sup> (24AWG)	0.44mm <sup>2</sup> (21AWG)
Temperature rating:	90°C	90°C

Price Per	RRP (m)	Roll	4 Rolls	
<b>Copper</b>				
W 2341	7/0.20 100m White	0.90	65.00	55.00
W 2364*	14/0.20 100m White	2.20	120.00	100.00
W 2355	14/0.20 200m Black	2.20	240.00	200.00
W 2365*	14/0.20 305m White	2.20	366.00	305.00

\*W 2364/65 ACMA approved for security applications

6 Core Security

305m lengths supplied in pull boxes. Other models supplied on reels. All white outer sheath.



	7/0.20	14/0.20
Current rating:	2.2A	4.5A
Size:	6 x 7/0.20	6 x 14/0.20
Outside diameter:	≈5.1mm	≈5.5mm
Resistance @ 20°C:	0.084Ω/m	0.042Ω/m
Conductor area:	0.22mm <sup>2</sup> (24AWG)	0.44mm <sup>2</sup> (21AWG)
Temperature rating:	90°C	90°C

Price Per	RRP (m)	Roll	4 Rolls	
<b>Copper</b>				
W 2360	7/0.20 200m	1.10	180.00	150.00
W 2370*	14/0.20 100m	2.80	145.00	125.00
W 2371*	14/0.20 305m	2.80	442.25	381.25

\*ACMA approved for security applications


▼ Solar Cable

Solar Photovoltaic Cable

Designed for use in solar panel systems. UV stabilised all weather, halogen free, double insulated construction. Super tough outer sheath impervious to oils & grease.



TUV certified.



Model	W 7015	W 7016
Size:	1 x 52/0.30	1 x 78/0.30
Rating:	42A	70A
Outside diameter:	≈6.0mm	≈6.5mm
Voltage AC:	0.6KV	0.6KV
Voltage DC:	1.8KV	1.8KV
Conductor:	4.0mm <sup>2</sup> (≈11AWG)	6.0mm <sup>2</sup> (≈9AWG)
Temperature rating:	-40 to 90°C	-40 to 90°C

Price Per	RRP (m)	1 Roll	
W 7015	4mm 100m	5.50	395.00
W 7016	6mm 100m	6.95	575.00