



Professional Audio Products

Australian Made Since 1974.

For more information on our range of Redback® products, visit www.redbackaudio.com.au

Redback® 15 Watt Stereo Amplifier



This super compact stereo amp is ideally suited to classrooms, boardrooms, boutiques, reception areas or anywhere a small functional stereo system is required. Offering outstanding stereo performance and featuring both stereo RCA aux and a 3.5mm input. Dual RCAs are provided on the rear panel for source input, whilst a 3.5mm jack is provided on the front panel (ideal for smartphone connection). A mono RCA output is provided for subwoofer connection. 240V AC operation. Suits 4 to 16 Ohm speakers.

- Features:** • 15W RMS per channel • 1 music input (3.5mm) • 1 auxiliary input • 4 - 16Ω output • 240V AC operation • Australian made

SPECIFICATIONS

Power Output:	15W RMS into 4Ω	Indicators:	Power, fault
Distortion:	< 3% @ 1kHz	Speaker output:	Pluggable terminals 4-16Ω
SN Ratio:	75dB below rated output	Sub out:	RCA mono 10kΩ
Frequency Response:	60Hz - 15kHz, -3dB	Input:	Stereo RCA, 3.5mm jack
Input Sensitivity:	1V	Power:	240V AC Fig 8 IEC
Controls:	Volume, treble, bass	Dimensions:	210W x 140D x 44Hmm

Price Each		RRP	2+
A 4116	15 Watt stereo amplifier	225.00	210.00
H 4990	Rack mounting kit	58.00	53.00
H 4991	Under desk bracket	15.50	14.00
H 4993	Half rack in-fill panel	18.95	17.95

Redback® 15 Watt Public Address Amplifier



Super compact with surprising performance specifications, intended for smaller PA system applications. Our engineering team based the design around a National TDA1519 monolithic IC achieving virtually "destruction proof" operation under quite severe misuse such as over temperature, over voltage, over load and short circuit speaker line conditions. The amplifier is extremely stable even where microphone (balanced line) and speaker cables are run together for long distances. Powered by 12-14V DC, making it well suited for use in tour buses and mobile installations.

- Features:** • 15W RMS output • Headphone socket • 1 balanced XLR and unbalanced jack mic input • Selectable phantom power on mic input • 1 aux input • Music input on front • 4-16Ω Output • Selectable Input Sensitivity • 12V DC operation (includes power supply)

SPECIFICATIONS

Power Output:	15W RMS into 4Ω	Indicators:	Power
Distortion:	< 3% @ 1kHz	Speaker output:	Pluggable terminals 4-16Ω
SN Ratio:	75dB below rated output	Mic 1 Input:	3 pin XLR bal., 6.35mm unbal.
Frequency Response:	50Hz - 10kHz, -3dB	Line Input:	Stereo RCA bridged mono
Input Sensitivity:	500mV (aux), 1.5mV (mic)	Power:	12V DC screw term./2.1mm skt.
Controls:	Volume (mic & line)	Dimensions:	210W x 130D x 44Hmm

Price Each		RRP	2+
A 4017	15 Watt amplifier	215.00	200.00
H 4990	Rack mounting kit	58.00	53.00
H 4991	Under desk bracket	15.50	14.00
H 4993	Half rack in-fill panel	18.95	17.95