

## Redback® 30W 2 Input 100V Public Address Amplifier

Designed to meet the requirements of small to medium sized professional public address installations, delivering an output power of 30W RMS. . With one balanced microphone and two stereo line inputs, with recessed treble and bass controls, it's perfect for simple installations requiring minimal inputs. Frequency response extends from 40Hz to 10kHz at a total harmonic distortion (THD) of less than 0.5%. Output is 100V line only. VOX circuit on input 1 mutes input 2. Features variable sensitivity and time delay setting. Size: 300W x 220D x 74H mm

**Features** • Balanced microphone input • Built in VOX muting circuit • Stereo line inputs • Bass and treble tone controls • 240V AC operation



Price Each	RRP	2+
A 4022 Desk mount	400.00	369.00

## Redback® 30W 3 Input 100V Public Address Amplifier

A staple of the Redback range since we first started, the 30W amplifier meets the requirements of small to medium public address installations. Features push to talk (PTT) auxiliary muting, three combined balanced microphone / stereo line inputs, tape out, and separate bass and treble controls. Offers a wide scope of installation applications, including schools, public halls, workshops and sporting complexes. Output may be 100V line or low impedance (8 - 16Ω) speaker loads. This unit features thermal overload shutdown, over current and short circuit protection.

Vox muting: The VOX circuit allows telephone paging via line input one or two (selectable internally). When paging via the telephone, all other line inputs are muted (ie. background music). Features variable sensitivity and time delay settings.

A 4024: 300W x 220D x 80H mm, A 4026: 483W x 220D x 88H mm

**Features** • Push to talk (PTT) muting on microphone 1. • Balanced microphone inputs. • VOX muting circuit. • Stereo line inputs & tape output. • Bass and treble tone controls. Output terminals for 100V line and 8 - 16Ω loads • Over-voltage, over current, thermal run-away and short circuit load protection.



A 4024 30W Desk Mount Model.

Price Each	RRP	2+
A 4024 Desk mount	460.00	415.00
A 4026 Rack mount	495.00	455.00

## Redback® Phase5 100V Public Address Amplifiers

Designed to meet the requirements of medium sized professional public address installations. Features include, VOX muting, three balanced XLR microphone inputs, three line RCA inputs, bass and treble controls, enabling a diversity of installation applications, including schools, public halls, workshops and sporting complexes. 423W x 225D x 88Hmm.

**A 4573 Alert/evac option board:** When fitted, generates pre chime, bell, alert and evacuation tones. The alert tone can function continuously, or switch to evac tone after a preset time delay (adjustable 30 seconds to 4.5 minutes). Simply connects to the amplifier internally via the cable provided.

**A 4373 Digital remote volume option board:** When fitted and used in conjunction with A 2280B wallplate to provide remote volume level adjustment. Ideal for situations where the amplifier is located in a remote rack.

**Features:** • 3 balanced microphone inputs • Phantom power on mic inputs • 3 line inputs • 19" rack mount kit included • VOX muting • Tape output RCA sockets • Bass and treble tone controls • 100V line output • 240V AC or 24V DC operation • Built in short circuit protection • 10 year warranty • Optional evac module available • Optional remote volume module



Price Each	RRP	2+
A 4037 40W	700.00	650.00
A 4043 60W	825.00	775.00
A 4047 100W	910.00	860.00
A 4573 Alert/evac option	150.00	130.00
A 4373 Remote volume module	91.95	
A 2280B Remote volume wallplate	28.25	

