

▼ Stereo Amplifiers

30W Mini Class-D Stereo Amplifier

This compact amplifier is a great way to power a pair of speakers without the bulk of a full size hi-fi receiver. It provides 2x15W RMS output power (4Ω) - enough to power a pair of small ceiling or bookshelf speakers. 6.35mm and 3.5mm inputs are provided for direct connection to a microphone or MP3 player. It could even be hooked up to a wireless Bluetooth adaptor (such as A 1102A) for audio streaming from your smartphone or tablet. Includes power supply. Size: 93W x 72D x 27Hmm.



Price Each	RRP	2+	4+
A 3043	99.00	89.00	79.00

4 Zone 30W Stereo Amplifier

Excellent for multi-room audio distribution, this 12V powered four zone amplifier produces 30W RMS per zone (15W RMS per channel) - all from a case just 200mm across! One input source may be connected on the front panel via stereo RCA sockets. An individual volume control is provided for each zone. Pluggable terminal blocks make output connection to speakers easy. A 3.5mm stereo headphone jack is provided with a dedicated volume control. Loop output allows connection of source input to additional amplifiers. Includes speaker protection circuitry. A quick and easy way to distribute an audio source, such as background music, around a home or business. **Please note: power supply is included**

SPECIFICATIONS

Amplifier type:	Class D stereo	Min load:	4Ω
Output power:	15W RMS per channel @ 4 ohm	Current draw:	9A max.
Distortion:	0.06%	Power:	12V DC
Headphone output:	105mW RMS per channel	Dimensions:	205W x 108D x 26Hmm
Headphone distortion:	0.05%	Weight:	0.5kg

Price Each	RRP	2+	4+
A 4198	275.00	250.00	225.00

4 Input 4 Zone 30W Stereo Amplifier

This integrated 4 zone amplifier and source switcher is designed to power up to 8 speakers and switch between four audio sources. Connection of sources is via 6.35mm jack (microphone), 3.5mm stereo jack, stereo RCA and S/PDIF digital (co-axial or optical). It's ideal for small businesses looking to provide background music, announcing etc using ceiling or wall speakers. Toslink audio connection is ideal for television audio. A local loop output and headphone jack connection is also provided. Each zone is fitted with its own level control to make adjustments in each area. Power supply included.

SPECIFICATIONS

Amplifier type:	Class D stereo	Min load:	4Ω
Output power:	15W RMS per channel @ 4 ohm	Current draw:	9A max.
Distortion:	0.06%	Power:	12V DC
Headphone output:	105mW RMS per channel	Dimensions:	285W x 128D x 43Hmm
Headphone distortion:	0.05%	Weight:	0.8kg

Price Each	RRP	2+	4+
A 4199	329.00	299.00	269.00

▼ Audio Sources

Redback® MP3 / USB / SD / CD Player With Pitch Control

This professional, rack mount CD player features an adjustable pitch control function. This allows the playback speed to be altered. Speed can be altered up or down in 10 steps. A wide variety of sources may be used including standard CD, MP3 CD, USB memory stick, SD card. A full function remote control is included. Particularly useful in aerobics or dance classes, function centres, clubs & entertainment venues etc.

Features • 1RU 19" rack mount • Pitch control function • LCD track & time display • 3.5mm front panel aux input • 32 track program • CD, USB or SD card playback • Forward or backward search and skip control • Gapless playback function • ID3 tag display • CD-R, CD-RW compatible • MP3/WMA compatible • 240V AC or 24VDC operation

Price Each	RRP	2+	4+
A 2733D	569.00	539.00	509.00

DAB+ FM Digital Tuner & Internet Radio Player

Access over 14,000 internet radio stations & podcasts from around the world, sorted by country and genre. This standalone device requires only an internet connection (no computer required). USB2.0 connection on the front panel allows playback of music from a memory stick. The unit is compatible with UPnP media streaming allowing you to playback music from your computer through your home hi-fi system. A standard FM tuner with RDS is also in-built providing even greater options for your music listening. Dimensions: 430 x 90 x 285 mm.

Features • DAB+ band III digital tuner and analog FM tuner • UPnP compatible - play music from PC's on your network • Internet radio station streaming • USB playback • MP3, AAC+, WMA-9 playback • Wired or wireless 802.11b/g

Price Each	RRP	2+	3+
A 2696	549.00	495.00	440.00

Redback® Dual AM/FM/DAB+ Tuner With RS-232 Control

This RS232 controlled dual radio tuner is ideal for multi zone audio systems requiring separate programming in each zone. It features one AM/FM tuner and one DAB+ tuner in the same compact 1RU chassis. It is controlled via front panel, infra red remote or a third party RS-232 control system allowing integration into distributed audio systems in complexes such as function centres, gymnasiums, entertainment venues, educational institutions etc. Individual RF aerial and RCA outputs are provided with rear mounted level controls for each tuner.

Features • IR remote control • DAB+ digital tuner • Dual outputs • Dual AM & FM analogue aerial inputs • Telescopic DAB+ antenna • Rear mounted level controls • 40AM/60FM pre-sets per tuner • Mono/stereo selector • RS-232 control • PLL synthesised tuner • LCD readout • 240V AC operation • Remote control

Price Each	RRP	2+
A 2704B	499.00	459.00