

4 Way HDMI 4K Switcher With Extractor & ARC



This compact 4-way HDMI switcher features manual & infra-red remote control for switching up to 4 sources to a single display supporting resolutions up to 4K/2K @ 60Hz. Ideal for home theatres, showrooms, boardrooms & lecture theatres. Includes power supply & remote control. Digital audio signals can be split from the HDMI signal with dedicated S/PDIF and coaxial outputs. The ARC function allows the audio from the selected display to be sent to the digital and 3.5mm jack outputs provided. HDMI 2.0. HDCP 2.2 compliant. Size: 154W x 70D x 24Hmm.

Price Each	RRP	2+	4+
A 3081E 4 input, 1 output	135.00	121.50	109.00

HDMI/HDBaseT Balun Matrix Switchers & Receiver



A 3549



A 3528 Balun Receiver Front & Rear Connections

Connects HDMI AV devices independently and switches each to HDMI equipped displays using the latest HDBaseT technology. HDBaseT allows these units to send full uncompressed audio and video over a single Cat6/7 UTP cable to the A 3528 receiver located in another room up to 100m away. Each receiver unit is fitted with RS-232 and infra-red (IR) for controlling source equipment remotely.

Each matrix switcher is fitted with RS-232 control port and IR extender port for easy remote source/monitor selection. RS-232 I/O connections are also provided for each HDBaseT zone output. Preset configurations can be stored in memory and recalled at a button press. All models are 4K/2K ready. 19" rack mountable (ears supplied). HDCP and HDMI 1.4 compliant. All units include power supplies. A 3528 Cat6 balun receivers are sold individually, each includes IR receiver, IR transmitter and power supply.

A 3549 dimensions: 482W x 250D x 44Hmm.

A 3559 dimensions: 442W x 300D x 176Hmm.

Note: We recommend a high quality Cat6/6a/7 cable for use with baluns up to 100m away. Do not use with CCA type UTP cable which does not support the data rate required for uncompressed HDMI signals.

- Features** • HDCP compliant • Supports uncompressed HDMI signal • Supports 340MHz /6.75Gbps • Supports 4K (24/30Hz) • Supports 3D 1.4a formats • Supports LPCM, DTS digital, Dolby Digital Plus, DTS-HD, Dolby True HD • Seven EDID modes • Simultaneous HDMI & Cat5e/6 output • Bi-directional infra-red signal pass through • RS-232 control inputs for each zone • Preset configuration memory • 100m Cat5e/6 balun range

Price Each	Shinybow Part	RRP
A 3549 4 In, 4 Out Balun 4K/2K	SB-5645CAK	1599.00
A 3559 16 In, 16 Out Balun 4K/2K	SB-5669CCK	8500.00
A 3528 Cat6 Balun Receiver	SB-6335R	225.50

Important Note For Wholesale Customers

All prices listed in this catalogue are RRP "retail" prices. To access our competitive wholesale pricing scheme apply for an account via www.altronics.com.au or phone the wholesale division in your state - see back cover for phone numbers..

HDMI Splitters

4K HDMI Splitters

Allows the connection of a single HDMI source to multiple HDMI displays with no loss of quality. Uses include home theatre, conference centres, sports bars etc. Includes power supply. HDCP compliant. 3D 4K x 2K, 12-bit deep colour and HD lossless audio support.



A 3128A

Price Each	RRP	3+	6+
A 3127 1 input, 2 output V1.4a 10.2Gbps Bandwidth	59.95	53.95	47.95
A 3134E 1 input, 2 output V2.0 18Gbps Bandwidth	89.95	80.95	71.95
A 3128A 1 input, 4 output V1.4a 10.2Gbps B/width (30Hz)	99.95	89.95	79.95

4K HDMI Splitters



A 3135E

Allows the connection of multiple HDMI displays to a single HDMI source (up to 4k) with no loss of signal quality. Uses include conference centres, sports bars, concerts, board rooms and other distributed AV applications where multiple displays are required. Multiple splitter units may be daisy chained together for connection to any number of displays. 3D HDMI 2.0 compatible. 18Gbps bandwidth. HDCP compliant. Includes power supply. A 3135E size: 154W x 69D x 23Hmm. A 3136C size: 211W x 65D x 26Hmm.

Price Each	RRP	3+	6+
A 3135E 1 input, 4 output	129.00	115.95	102.95
A 3136C 1 input, 8 output	259.00	233.00	207.00

1 In To 16 Out HDMI V2.0 4K Splitter



Allows the connection of up to 16 HDMI displays to a single HDMI source (up to 4K @ 60Hz each) with no loss of signal quality. Applications include conference centres, sports bars, concerts, board rooms or anywhere multiple displays are required. Multiple splitter units may be daisy chained together for connection to any number of displays. Includes IR remote control, power supply and 19" rack mount ears. Dimensions: 440W x 200D x 45Hmm. HDCP compliant.

Price Each	RRP	2+	3+
A 3137B 1 input, 16 output V2.0	849.00	765.00	699.00

Toslink Switcher

4 Way Auto Toslink Switcher

Provides automatic switching between up to 4 Toslink S/PDIF digital audio inputs. When a signal is present the switcher will switch to the port automatically. Manual selection is also available. Works with CD, BluRay, game consoles and other digital audio sources. Supports PCM/LPCM and bitstream Dolby AC-3, Dolby 5.1, Dolby Digital and DTS. Includes power supply.



Price Each	RRP	2+	4+
A 3212 4 input, 1 output	85.95	77.50	68.95