

▼ Lectern Microphones

Dynamic Insert Gooseneck Microphone

A microphone featuring speech tailored frequency response with excellent noise isolation and feedback rejection. Complete with flexible gooseneck and built in 3 pin male XLR connector, it is suitable for lecterns, custom paging consoles, church pulpits and some mixers. Features a 3 pin XLR connector.

Impedance: 600Ω balanced, dynamic
Sensitivity: -80dB ±3dB
Frequency response: 150Hz - 12kHz
Length: ≈450mm
Polar pattern: Cardioid (unidirectional)



No wiring needed.
Simply plugs into
an XLR socket!

Price Each **C 0370** RRP 80.00 2+ 69.25

Dynamic Insert Gooseneck Microphone With PTT

A high performance dynamic microphone with in-built PTT switch in the head for paging systems. Complete with flexible gooseneck and built in 3 pin male XLR connector, it is ideal for paging consoles and general announcing requirements in factories, warehouses, food outlets and venues.

Impedance: 500Ω balanced, dynamic
Sensitivity: -80dB ±3dB
Frequency response: 60Hz - 12kHz
Length: ≈460mm
Polar pattern: Cardioid (unidirectional)



No wiring needed.
Simply plugs into
an XLR socket!

Price Each **C 0354** RRP 149.00 2+ 139.00

Dynamic Insert Gooseneck Microphone with On/Off Switch

Featuring outstanding speech intelligibility, feedback rejection and user sound isolation. Complete with flexible gooseneck and built in 3 pin male XLR connector, it is designed for lecterns, custom paging consoles & church pulpits. The flexible gooseneck is unobtrusive yet rigid enough to remain in position once adjusted. Includes a 3 pin XLR connector

Insert: Dynamic
Impedance: 500Ω balanced
Sensitivity: -77dB ±3dB
Frequency response: 100Hz - 12kHz
Length: ≈420mm
Polar pattern: Cardioid (unidirectional)



No wiring needed.
Simply plugs into
an XLR socket!

Base fitted with On / Off switch.

Price Each **C 0373** RRP 125.00 2+ 115.00

Dynamic Screw Mount Gooseneck Microphone

An elegant gooseneck microphone delivering superb natural speech reproduction with excellent background noise cancellation and low feedback incidence. Its 5/8th inch threaded screw base is suitable for mounting on equipment or permanent desk mounting. The slimline design is perfect for custom paging consoles. 200mm flying leads.

Impedance: 500Ω
Sensitivity: -76dB ±3dB
Frequency response: 100Hz-10kHz
Length: ≈325mm
Polar pattern: Cardioid (unidirectional)



Price Each **C 0363** RRP 115.00 2+ 105.00

Electret Insert Gooseneck Microphone

This elegant gooseneck microphone features smooth, brilliant sound with excellent ambient noise control and feedback rejection. Ideal for installations requiring a high performance unobtrusive microphone. The slimline design is suited to custom paging consoles, lecterns & podiums. Equipped with a 3 pin XLR. Requires phantom supply - see page 93.

Impedance: 250Ω electret
Sensitivity: -63dB ±3dB
Frequency response: 70Hz-16kHz
Length: ≈425mm
Polar pattern: Cardioid (unidirectional)
Voltage: 9 - 52 Volts DC



No wiring needed.
Simply plugs into
an XLR socket!

Price Each **C 0369** RRP 165.00 2+ 149.00

Gooseneck Shotgun Microphone

A shotgun mic designed to plug directly into a desk mount XLR socket. The line + gradient pattern provides an extremely tight unidirectional pickup and high rejection of back & side signals. It features a section of flexible gooseneck for angle adjustment. Phantom powered by 9 - 52V DC.

Insert: Electret
Impedance: 200Ω balanced
Sensitivity: -60dB ±3dB
Frequency response: 30Hz - 18kHz
Length: ≈288mm



Price Each **C 0361** RRP 179.00 2+ 165.00
C 0347 Spare windsock to suit 12.75

Redback® audio products have a dedicated home online...

www.redbackaudio.com.au

A resource for installers, consultants and specifiers to find information on the entire range of Redback public address equipment. You can even find system diagrams and helpful articles to make your installation easier.

