

Introduction

This Digital to Analog Audio Converter is designed for either home or professional audio switching. It converts Coaxial or Toslink digital audio signals to analog L/R audio and available for connection to an external device such as an amplifier via standard RCA-style jacks. This Converter is small in size and quite easy to install.

Features

This Converter has many features that enable it to perform in a superior manner. Among those features you will find:

- 1、Converts Coaxial or Toslink digital audio signals to analog L/R audio
- 2、Supports sampling rate at 32, 44.1, 48 and 96 KHz.
- 3、24-bit S/PDIF incoming bit stream on left and right channels
- 4、Provides electromagnetic-noise-free transmission.
- 5、Easy to install and simple to operate.

SPECIFICATIONS

Signal Inputs/Output	
Input Audio	Coaxial or Toslink digital audio
Output Audio	L/R audio
Connector	
Input audio connector	Toslink、1XRCA(Coaxial)
Output audio connector	2XRCA (R/L)
Sampling rate	32, 44.1, 48 and 96 KHz
Mechanical	
Size(L-W-H)	51X41X26MM
Weight (Net)	78g
Warranty	
Limited Warranty	1 Year Parts and Labor
Environmental	
Operating Temperature	0 °C to +70°C

Operating Humidity	10% to 85 % RH (no condensation)
Storage Temperature	-10℃ to +80℃
Storage Humidity	5% to 90 % RH (no condensation)
Power Requirement	
External Power Supply	5V DC@2A
Power Consumption	0.5 watts (max)
Regulatory Approvals	
Converter Unit	FCC,CE,UL
Power Supply	UL,CE,FCC
Accessories Adapter	
AC Power Adapter	US standard, UK standard and so on
User Manual	English Version

