

Operating Manual of Intelligent Digital Tachometer

I. Characteristics

- 1. Beautiful and elegant appearance design, convenient and comfortable to use;
- 2. Wide measurement range, and high resolution;
- 3. Single-chip microcomputer technology, photoelectric technology and anti-interference technology used, to accurately measure the rotation speed;
- 4. Super large-size LCD, with clear reading;
- 5. Automatically memorizing the measured maximum, minimum and the last displayed values;
- 6. Low power indication when the battery voltage is lower than the specified value;
- 7. Automatic off: Automatic off in about 15min when no key is operated.

II. Specifications

Function	
Photoelectric type	Δ

Note: Each model adopts the following technical indicators and operation methods according to functions in the table.

Display:	5-digit 18mm LCD
Accuracy:	± (0.05%+1)
Range selection:	Automatic range
Effective distance:	50mm-500mm
Dimension:	150mm*65mm*31mm
Power supply:	4*1.5V AAA batteries
Power consumption:	Less than 40mA
Weight:	About 156g (including batteries)
Measurement range:	2.5-99999 rpm for photoelectric rotation speed
Resolution:	Photoelectric rotation speed: 0.1rpm (2.5-999.99rpm) 1rpm (above 1000rpm)

III. Operation Instructions

1. Starting up

Load four 1.5V AAA batteries (the anode and cathode directions according to the identifications in the battery case). Long press ON/OFF key to switch it on or off.

2. Photoelectric rotation speed:

- A: Stick one reflective marker on the object to measure.
- B: Long press ON/OFF to switch it on and displays “photo RPM”

- measurement mode after being switched on.
- C. Press TEST key to make the visible beam and the measured target in a line. Release the TEST key after the displayed value stabilizes and the measured maximum, minimum and the last displayed values will be automatically stored in the instrument.
- D. Press MEM key to display the maximum, minimum and the last measured values.

3. Measurement Notes

A: Reflective marker: Cut off 12mm square adhesive tapes, and stick one on each rotation axis. Pay attention that the non-reflective area shall be larger than the reflective area. If the rotation axis obviously gives out light, first smear it with black paint or stick black tape, and then stick reflective marker thereon; rotation axis surface must be clean and smooth before sticking of the reflective marker.


B: Measurement of low rotation speed: To improve the measurement accuracy, user is recommended to evenly stick more reflective markers on the measured object when the rotation speed is very low, and then divide the reading on the display by the number of reflective markers to obtain the actual measured value.

C. Please take out the batteries if not to use the instrument for a long time, so as to avoid damaging the instrument by corroded batteries.

4. Description of MEM Function

When TEST key is released, the display will display “0” and current measurement mode, but the measured maximum, minimum and the last measured values are automatically stored in the instrument, and at this time, press MEM key for it to display the measured values, wherein “MAX” means maximum, “MIN” means minimum, and “LA” means the last value. Each time the MEM is pressed, another memorized value will be displayed.

5. Battery Replacement

A. When batteries are lower than 3.7V, LCD will display  icon to prompt for battery replacement.

B. Open the battery cover and take out batteries, and then correctly install batteries according to the identifications in the battery case.

Accessories:

Reflective tape	600mm long
Manual	1 copy