

# Dy-Mark Protech Freeze Spray 300g

Dy-Mark

Chemwatch: 42-9973 Version No: 7.1.1.1

Safety Data Sheet according to WHS and ADG requirements

# Chemwatch Hazard Alert Code: 1

Issue Date: 01/11/2019 Print Date: 23/01/2020 S.GHS.AUS.EN

# SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### **Product Identifier**

Product name	Dy-Mark Protech Freeze Spray 300g
Chemical Name	1,1,1,2-tetrafluoroethane
Synonyms	42033004
Proper shipping name	AEROSOLS
Other means of identification	Not Available

# Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Application is by spray atomisation from a hand held aerosol pack
ivelevani identined uses	Use according to manufacturer's directions.

# Details of the supplier of the safety data sheet

Registered company name	Dy-Mark
Address	89 Formation Street Wacol QLD 4076 Australia
Telephone	+61 7 3327 3004
Fax	+61 7 3327 3009
Website	http://www.dymark.com.au
Email	info@dymark.com.au

# **Emergency telephone number**

Association / Organisation	Dy-Mark
Emergency telephone numbers	+61 7 3327 3099
Other emergency telephone numbers	Not Available

# **SECTION 2 HAZARDS IDENTIFICATION**

# Classification of the substance or mixture

# HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

## CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	0		
Toxicity	1		0 = Minimum
Body Contact	1		1 = Low 2 = Moderate
Reactivity	1		3 = High
Chronic	Λ.		4 = Extreme

Poisons Schedule	Not Applicable
Classification <sup>[1]</sup>	Not Applicable

Label elements		
Hazard pictogram(s)	Not Applicable	
SIGNAL WORD	NOT APPLICABLE	
Upperd statement(s)		

Hazard statement(s)	
AUH044	Risk of explosion if heated under confinement.

# Supplementary statement(s)

Not Applicable

Dy-Mark Protech Freeze Spray 300g

Issue Date: **01/11/2019**Print Date: **23/01/2020** 

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

#### **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
811-97-2	100	1.1.1.2-tetrafluoroethane

## **SECTION 4 FIRST AID MEASURES**

#### Description of first aid measures

Eye Contact	If aerosols come in contact with the eyes:  Immediately hold the eyelids apart and flush the eye with fresh running water.  Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  Seek medical attention without delay; if pain persists or recurs seek medical attention.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If solids or aerosol mists are deposited upon the skin:  Flush skin and hair with running water (and soap if available).  Remove any adhering solids with industrial skin cleansing cream.  DO NOT use solvents.  Seek medical attention in the event of irritation.
Inhalation	If aerosols, fumes or combustion products are inhaled:  Remove to fresh air.  Lay patient down. Keep warm and rested.  Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.  If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.  Transport to hospital, or doctor.
Ingestion	Not considered a normal route of entry.  Avoid giving milk or oils.  Avoid giving alcohol.  If conscious, give water to drink.

## Indication of any immediate medical attention and special treatment needed

for intoxication due to Freons/ Halons;

- A: Emergency and Supportive Measures
- Maintain an open airway and assist ventilation if necessary
- ► Treat coma and arrhythmias if they occur. Avoid (adrenaline) epinephrine or other sympathomimetic amines that may precipitate ventricular arrhythmias. Tachyarrhythmias caused by increased myocardial sensitisation may be treated with propranolol, 1-2 mg IV or esmolol 25-100 microgm/kg/min IV.
- ▶ Monitor the ECG for 4-6 hours
- B: Specific drugs and antidotes:
- There is no specific antidote
- C: Decontamination
- Inhalation; remove victim from exposure, and give supplemental oxygen if available.
- Ingestion; (a) Prehospital: Administer activated charcoal, if available. DO NOT induce vomiting because of rapid absorption and the risk of abrupt onset CNS depression. (b) Hospital: Administer activated charcoal, although the efficacy of charcoal is unknown. Perform gastric lavage only if the ingestion was very large and recent (less than 30 minutes)
- D: Enhanced elimination:

   There is no documented efficacy for diuresis, haemodialysis, haemoperfusion, or repeat-dose charcoal

POISONING and DRUG OVERDOSE, Californian Poison Control System Ed. Kent R Olson; 3rd Edition

- ▶ Do not administer sympathomimetic drugs unless absolutely necessary as material may increase myocardial irritability.
- ▶ No specific antidote.
- Because rapid absorption may occur through lungs if aspirated and cause systematic effects, the decision of whether to induce vomiting or not should be made by an attending physician.
- ▶ If lavage is performed, suggest endotracheal and/or esophageal control.
- ► Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach.
- ▶ Treatment based on judgment of the physician in response to reactions of the patient

Treat symptomatically.

# **SECTION 5 FIREFIGHTING MEASURES**

## Extinguishing media

Issue Date: 01/11/2019 Print Date: 23/01/2020

#### SMALL FIRE:

► Water spray, dry chemical or CO2

#### LARGE FIRE:

Water spray or fog.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
Advice for firefighters	
Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>May be violently or explosively reactive.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered to be a significant fire risk.</li> <li>Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>Aerosol cans may explode on exposure to naked flames.</li> <li>Decomposition may produce toxic fumes of:</li> <li>Combustion products include:</li> <li>carbon dioxide (CO2)</li> <li>hydrogen fluoride</li> </ul>

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

## **SECTION 6 ACCIDENTAL RELEASE MEASURES**

HAZCHEM

# Personal precautions, protective equipment and emergency procedures

Not Applicable

See section 8

#### **Environmental precautions**

See section 12

#### Methods and material for containment and cleaning up

wetnods and material for containment and cleaning up		
Minor Spills	<ul> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Wear protective clothing, impervious gloves and safety glasses.</li> <li>Shut off all possible sources of ignition and increase ventilation.</li> </ul>	
Major Spills	<ul> <li>DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.</li> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>May be violently or explosively reactive.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Remove leaking cylinders to a safe place if possible.</li> <li>Release pressure under safe, controlled conditions by opening the valve.</li> </ul>	

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## **SECTION 7 HANDLING AND STORAGE**

Other information

## Precautions for safe handling

▶ Avoid all personal contact, including inhalation. ► Wear protective clothing when risk of exposure occurs. Safe handling

Use in a well-ventilated area.

other pyrolysis products typical of burning organic material

Prevent concentration in hollows and sumps.

▶ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can

## Conditions for safe storage, including any incompatibilities

► DO NOT use aluminium or galvanised containers Suitable container

Aerosol dispenser.

► Check that containers are clearly labelled

Storage incompatibility

► Avoid reaction with oxidising agents Avoid strong acids, bases

Avoid contamination of water, foodstuffs, feed or seed.















— Must not be stored together

0 — May be stored together with specific preventions

May be stored together

#### **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

Issue Date: 01/11/2019 Print Date: 23/01/2020

#### **Control parameters**

Version No: 7.1.1.1

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	1,1,1,2-tetrafluoroethane	1,1,1,2-Tetrafluoroethane	1000 ppm / 4240 mg/m3	Not Available	Not Available	Not Available

#### **EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
1,1,1,2-tetrafluoroethane	HFC 134a; (Tetrafluoroethane, 1,1,1,2-)	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
1,1,1,2-tetrafluoroethane	Not Available	Not Available

#### **Exposure controls**

#### Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment

#### Personal protection









No special equipment for minor exposure i.e. when handling small quantities.

OTHERWISE: For potentially moderate or heavy exposures:

- - ▶ NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.
  - Close fitting gas tight goggles
  - Safety glasses with side shields.

Safety glasses with side shields.

- Chemical goggles.
- Contact lenses may pose a special hazard: soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

## Skin protection

Eye and face protection

See Hand protection below

Wear general protective gloves, eg. light weight rubber gloves. No special equipment needed when handling small quantities.

- ► OTHERWISE:
- Hands/feet protection ▶ For potentially moderate exposures:
  - ▶ Wear general protective gloves, eg. light weight rubber gloves.
  - For potentially heavy exposures
  - ▶ Wear chemical protective gloves, eg. PVC. and safety footwear.

No special equipment needed when handling small quantities.

## **Body protection**

See Other protection below

OTHERWISE: Overalls

- Other protection
- Skin cleansing cream.
- Eyewash unit.

#### Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	Air-line*	AX-2	AX-PAPR-2 ^
up to 10 x ES	-	AX-3	-
10+ x ES	-	Air-line**	-

- \* Continuous Flow; \*\* Continuous-flow or positive pressure demand
- ^ Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask smell, have triggered allergic reactions in predisposed individuals.

Page 5 of 9

Dy-Mark Protech Freeze Spray 300g

Issue Date: **01/11/2019**Print Date: **23/01/2020** 

#### **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

#### Information on basic physical and chemical properties

Appearance	Colourless liquid with an ethereal-like odour; not miscible with water.		
Physical state	Liquid	Relative density (Water = 1)	1.212
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	-26.4	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	100
Vapour pressure (kPa)	583 @25C	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	>1	VOC g/L	Not Available

#### **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	<ul> <li>Elevated temperatures.</li> <li>Presence of open flame.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

#### **SECTION 11 TOXICOLOGICAL INFORMATION**

Inhaled

Skin Contact

#### Information on toxicological effects

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.

Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Exposure to fluorocarbons can produce non-specific flu-like symptoms such as chills, fever, weakness, muscle pain, headache, chest discomfort, sore throat and dry cough with rapid recovery. High concentrations can cause irregular heartbeats and a stepwise reduction in lung capacity. Inhalation of toxic gases may cause:

- ▶ Central Nervous System effects including depression, headache, confusion, dizziness, stupor, coma and seizures;
- respiratory: acute lung swellings, shortness of breath, wheezing, rapid breathing, other symptoms and respiratory arrest;
- ▶ heart: collapse, irregular heartbeats and cardiac arrest;
- gastrointestinal: irritation, ulcers, nausea and vomiting (may be bloody), and abdominal pain.

Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure.

Symptoms of asphyxia (suffocation) may include headache, dizziness, shortness of breath, muscular weakness, drowsiness and ringing in the ears. If the asphyxia is allowed to progress, there may be nausea and vomiting, further physical weakness and unconsciousness and, finally, convulsions, coma and death.

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.

Acute intoxication by halogenated aliphatic hydrocarbons appears to take place over two stages. Signs of a reversible narcosis are evident in the first stage and in the second stage signs of injury to organs may become evident, a single organ alone is (almost) never involved.

Overexposure is unlikely in this form.

Ingestion

Not normally a hazard due to physical form of product.

Considered an unlikely route of entry in commercial/industrial environments

Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.

There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.

Spray mist may produce discomfort Fluorocarbons remove natural oils from the skin, causing irritation, dryness and sensitivity. Open cuts, abraded or irritated skin should not be exposed to this material

Version No: 7.1.1.1

## Dy-Mark Protech Freeze Spray 300g

Issue Date: 01/11/2019 Print Date: 23/01/2020

Еуе	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).  Not considered to be a risk because of the extreme volatility of the gas.		
Chronic	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.  Main route of exposure to the gas in the workplace is by inhalation.  Fluorocarbons can cause an increased risk of cancer, spontaneous abortion and birth defects.		
Dy-Mark Protech Freeze Spray	TOXICITY  Not Available	IRRITATION  Not Available	
1,1,1,2-tetrafluoroethane  Legend:	TOXICITY  Inhalation (rat) LC50: 1500 mg/l/4h <sup>[2]</sup> Not Available  1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances		
1,1,1,2- TETRAFLUOROETHANE	* with added oxygen - ZhongHao New Chemical Mate concentrations of decomposition products can cause		can have a narcotic effect; inhalation of high
Dy-Mark Protech Freeze Spray 300g & 1,1,1,2- TETRAFLUOROETHANE	Disinfection byproducts (DBPs) are formed when disinfectants such as chlorine, chloramines and ozone react with organic and inorganic matter in water. Animal studies have shown that some DBPs cause cancer. To date, several hundred DBPs have been identified.  Numerous haloalkanes and haloalkenes have been tested for cancer-causing and mutation-causing activities. In general, the potential to cause genetic toxicity is dependent on the nature, number and position of halogen(s) and the size of the molecule.		
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	X
Serious Eye Damage/Irritation	×	STOT - Single Exposure	X
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

★ - Data either not available or does not fill the criteria for classification

— Data available to make classification

## **SECTION 12 ECOLOGICAL INFORMATION**

# Toxicity

Dy-Mark Protech Freeze Spray 300g	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	29.671mg/L	3
1,1,1,2-tetrafluoroethane	EC50	48	Crustacea	980mg/L	5
	EC50	96	Algae or other aquatic plants	97.260mg/L	3
	NOEC	72	Algae or other aquatic plants	ca.13.2mg/L	2
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

In addition to carbon dioxide (CO2), methane (CH4) and nitrous oxide (N2O), the greenhouse gases mentioned in the Kyoto Protocol include synthetic substances that share the common feature of being highly persistent in the atmosphere and inhibit radiation from escaping out of the atmosphere. These synthetic substances include hydrocarbons that are partially fluorinated (HCFs) or totally fluorinated (PFCs) as well as sulfur hexafluoride (SF6). The greenhouse potential of these substances, expressed as multiples of that of CO2, are within the range of 140 to 11,700 for HFCs, from 6500 to 9,200 for PFCs and 23,900 for SF6. Once emitted into the atmosphere, these substances have an impact on the environment for decades, centuries, or even for thousands of years.

DO NOT discharge into sewer or waterways.

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
1,1,1,2-tetrafluoroethane	HIGH	HIGH

# Bioaccumulative potential

Ingredient	Bioaccumulation
1,1,1,2-tetrafluoroethane	LOW (LogKOW = 1.68)

## Mobility in soil

Ingredient	Mobility
1,1,1,2-tetrafluoroethane	LOW (KOC = 96.63)

## Dy-Mark Protech Freeze Spray 300g

Issue Date: 01/11/2019 Print Date: 23/01/2020

# **SECTION 13 DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Product / Packaging disposal

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ► Where in doubt contact the responsible authority.
- ► Consult State Land Waste Management Authority for disposal.
- ▶ Discharge contents of damaged aerosol cans at an approved site.
- ▶ Allow small quantities to evaporate.
- ► DO NOT incinerate or puncture aerosol cans.

# **SECTION 14 TRANSPORT INFORMATION**

## **Labels Required**



Marine Pollutant

NO

HAZCHEM

Not Applicable

## Land transport (ADG)

UN number	1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	Class 2.2 Subrisk Not Applicable
Packing group	Not Applicable
Environmental hazard	Not Applicable
Special precautions for user	Special provisions   63 190 277 327 344 381

# Air transport (ICAO-IATA / DGR)

UN number	1950				
UN proper shipping name	Aerosols, non-flammable; Aerosols, non-flammable (containing biological products or a medicinal preparation which will be deteriorated by a heat test)				
Transport hazard class(es)	ICAO/IATA Class				
	ICAO / IATA Subrisk	/ IATA Subrisk Not Applicable			
	ERG Code	ERG Code 2L			
Packing group	Not Applicable				
Environmental hazard	Not Applicable				
	Special provisions		A98 A145 A167 A802		
	Cargo Only Packing Instructions		203		
	Cargo Only Maximum Qty / Pack		150 kg		
Special precautions for user	Passenger and Cargo Packing Instructions		203		
	Passenger and Cargo Maximum Qty / Pack		75 kg		
	Passenger and Cargo Limited Quantity Packing Instructions		Y203		
	Passenger and Cargo Limited Maximum Qty / Pack		30 kg G		

## Sea transport (IMDG-Code / GGVSee)

UN number	1950		
UN proper shipping name	AEROSOLS		
Transport hazard class(es)	IMDG Class 2.2  IMDG Subrisk Not Applicable		
Packing group	Not Applicable		
Environmental hazard	Not Applicable		
Special precautions for user	EMS Number         F-D , S-U           Special provisions         63 190 277 327 344 381 959		

Issue Date: **01/11/2019**Print Date: **23/01/2020** 

Limited Quantities 1000 ml

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Version No: 7.1.1.1

#### **SECTION 15 REGULATORY INFORMATION**

## Safety, health and environmental regulations / legislation specific for the substance or mixture

#### 1,1,1,2-TETRAFLUOROETHANE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List

Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes

Australia Dangerous Goods Code (ADG Code) - Packing Instruction - Liquefied and

Dissolved Gases

International Maritime Dangerous Goods Requirements (IMDG Code)
United Nations Recommendations on the Transport of Dangerous Goods Model
Regulations

Australia Inventory of Chemical Substances (AICS)

International Air Transport Association (IATA) Dangerous Goods Regulations

Australia Exposure Standards

#### **National Inventory Status**

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (1,1,1,2-tetrafluoroethane)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

## **SECTION 16 OTHER INFORMATION**

Revision Date	01/11/2019
Initial Date	15/09/2014

#### **SDS Version Summary**

Version	Issue Date	Sections Updated
5.1.1.1	24/06/2016	Name
7.1.1.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

 ${\sf PC-STEL} : {\sf Permissible Concentration-Short Term \ Exposure \ Limit}$ 

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit $_{\circ}$ 

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without

Chemwatch: 42-9973 Page 9 of 9 Version No: 7.1.1.1

Dy-Mark Protech Freeze Spray 300g

written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 01/11/2019

Print Date: 23/01/2020